




Area of Refuge
Systems

AlphaRefuge™

2100 Series

The ADA Compliant Solution for Buildings with up to 10 Remote Call Boxes



Meets all requirements of IBC, ADA, ASME and NFPA



Proudly Made
in the U.S.A.

REFUGE COMMAND CENTERS (Masters)



Proudly Made
in the U.S.A.



◀ RCC2510SF / RCC2510SS

Choose from the following Stainless Steel Masters:

- RCC2505SF - 5 Remote Max Flush Command Center**
O.D. : 11.875"W X 15.00"H X 3.25"D (mm: 302 W X 381 H X 83 D)
- RCC2505SS - 5 Remote Max Surface Command Center & Backbox**
O.D. : 11.75"W X 12.75"H X 5.50"D (mm: 298W X 324 H X 140 D)
- RCC2510SF - 10 Remote Max Flush Command Center**
O.D. : 11.875"W X 15.00"H X 3.25"D (mm: 302 W X 381 H X 83 D)
- RCC2510SS - 10 Remote Max Surface Command Center & Backbox**
O.D. : 12.50"W X 13.75"H X 4.50"D (mm: 318 W X 350 H X 115 D)

Standard Features

- Choose from 8 different finish/mounting/capacity combinations to best fit your specific application.
- Battery back-up allows for up to 4 hours of full operation upon loss of power.
- Requires standard 120vac supply and analog telephone line (either POTS, PBX or central office phone line). If used on a digital system must order an ATA analog telephone adapter ABL-VOIP.
- Easy to use push buttons.
- Passively monitor communications between phones and outside world via the LEDs.
- Solid lit LED indicates there is an emergency call in progress:
 - Slow blinking LED indicates there is a call on hold,
- Audible alert when phone initiates call, silenced when call is joined from the Master
- Different communication methods:
 - 1) Master phone can call into all or individual call box(es) as needed
 - 2) Can join in existing conversations between call box(es) and outside world
 - 3) Can hang-up and original conversation will continue



▶ PWR2410A Remote Power Supply 1 Per System for Remote Power (Up to 10 Remote Call Boxes)

O.D. : 8.125"W X 9.275"H X 3.75"D
(mm: 207 W X 236 H X 96 D)

◀ RCC2505CF



Choose from these Powder Coat, Lockable* Cabinet Masters:

- RCC2505CF - 5 Remote Max Flush Command Center**
O.D. : 14.00"W X 16.125"H X 6.15"D (mm: 356 W X 410 H X 157 D)
- RCC2505CS - 5 Remote Max Surface Command Center**
O.D. : 11.875"W X 14.75"H X 6.125"D (mm: 302 W X 375 H X 156 D)
- RCC2510CF - 10 Remote Max Flush Command Center**
O.D. : 14.00"W X 16.125"H X 6.15"D (mm: 356 W X 410 H X 157 D)
- RCC2510CS - 10 Remote Max Surface Command Center**
O.D. : 11.875"W X 14.75"H X 6.125"D (mm: 302 W X 375 H X 156 D)

* Locks & Keys Not Included.

REFUGE CALL BOXES (Remotes)

AlphaRefuge™
2100 Series



RCB2100RR
**Red Powder Coat
Finished Call Box**
O.D. : 4.75"W X 7.25"H X 1.875"D
(mm: 121 W X 185 H X 48 D)



RCB2100NR
**Red Fiberglass NEMA 4 Rated
Outdoor Surface Call Box**
O.D. : 6.00"W X 9.50"H X 2.875"D
(mm: 153 W X 242 H X 74 D)



RCB2100NRCOV
**Red Fiberglass NEMA 4 Rated
Outdoor Surface Call Box with
Protective Cover**
O.D. : 6.60"W X 9.90"H X 3.25"D
(mm: 168 W X 251 H X 83 D)
Cover: 3.75"W X 6.40"H X 2.25"D
(mm: 95W X 163 H X 57.15 D)



RCB2100SFR
**Brushed Stainless Steel
Flush Call Box**
O.D. : 7.50"W X 9.50"H X .50"D
(mm: 191 W X 241 H X 13 D)
I.D. : 6.00"W X 8.00"H X 3.00"D
(mm: 152 W x 203 H x 76 D)



RCB2100SFCOV
**Brushed Stainless Steel Flush
Call Box With Protective Cover**
O.D. : 8.00"W X 11.375"H X 2.00"D
(mm: 203 W x 289 H x 51 D)
I.D. : 6.50"W X 8.875"H X 3.00"D
(mm: 165 W x 225 H x 76 D)
Cover : 6.125"W X 9.90"H X 1.75"D
(mm: 156 W x 251 H x 44 D)



RCB2100SR
**Brushed Stainless Steel
Surface Call Box**
O.D. : 4.75"W X 7.25"H X 1.875"D
(mm: 121 W X 185 H X 48 D)



RCB2100SRCOV
**Brushed Stainless Steel Surface
Call Box With Protective Cover**
Face Plate: 6.70"W X 10.00"H
(mm: 170 W x 254 H)
BackBox: 6.50"W X 9.875"H X 2.30"D
(mm: 165 W x 251 H x 58 D)
Cover : 6.125"W X 9.90"H X 1.75"D
(mm: 156 W x 251 H x 44 D)



Proudly Made
in the U.S.A.

NOTE: Some models also available with mushroom-head buttons. Please contact us for more information.



Area of Refuge **AlphaRefuge™** Signage

2100 Series



Proudly Made
in the U.S.A.



Blue Wall Signs w/ Arrow

RSN7047R: Right Arrow
RSN7047L: Left Arrow
15.0"W X 5.0"H

Depending on the size of the building, an AHJ may require direction signage to get the occupants to the location.



Photoluminescent Wall Sign

RSN7041
8.00"W X 8.00"H X 0.25"D



Blue Wall Signs w/ Braille

RSN7044
6.0"W X 9.0"H

If Exit sign illumination is required, Area of Refuge signs must be illuminated as well. Signs shall be mounted at Entrance of Area of Refuge usually under 80" to comply with character and proportion sizes.



RSN7087
8.0"W X 8.0"H

Tactile signage or raised letter & braille signage is required at the entrance of the area of refuge to designate the area as such.

Red Lighted Refuge Sign

RSN7050 - 120VAC
14.0" W x 10.5" H x 3.00" D
Includes Battery Backup



White Wall Sign w/ Braille

RSN7043
6.0"W X 9.0"H

Photoluminescent Wall Sign w/ Braille

RSN7046
8.00"W X 8.00"H X 0.25"D



Some AHJs will accept this sign to take the place of the RSN7041 and RSN7044 so you only need one of these at the entrance to the area of refuge.

Instructions on the use of the area during an emergency are required in the actual area of refuge (we recommend next to the call box). 1007.11 is the section of the code that requires this.



Instruction Sign w/ Braille

RSN7049
6.0"W X 8.0"H

Self-Stick Floor Decal

RSN7045
17.0" Diameter

A large floor decal is typically not required, but it makes locating an Area of Refuge much easier, especially for people with impaired vision, or in limited sight situations.



42 Central Drive - Farmingdale NY 11735-1202
Phone: 631-777-5500 Fax: 631-777-5599
TOLL-FREE: 800-666-4800
www.AlphaCommunications.com

Available From: