
nVent CADDY Cat CM Double J-Hook – CAT100CM





- Provides optimal support for high-performance data cable, up to and including Cat 5e, Cat 6, Cat 6A, Cat 7 and fibre optic
- System offers a convenient pathway for wires and cables
- Double J-Hooks can be mounted vertically along the same drop rod to create a tree configuration
- Allows addition of cables even when fixed flush to overhead decking
- Specially designed double J-Hook has large-diameter, rounded support surfaces
- Rounded edges help prevent over-bending and kinking of cables
- Ideal for retrofit applications where cable runs need to be routed around existing building infrastructure
- Compliant with NEC[®] and ANSI[®]/TIA structured cabling systems standards





Part Number	CAT100CM
Material	Steel
Finish	Electrogalvanized
Cable Capacity, Cat 5e	70
Cable Capacity, Cat 6	50
Cable Capacity, Cat 6A	30
A	7 1/4"
Area	3.16 in ²
Hole Size (HS)	3/8"
Certifications	cULus
Standard Packaging Quantity	20 рс
UPC	78285646614
EAN-13	8711893003222

Area shown is the combined value for both sides. Divide by 2 for area of each side.

ANSI is a registered trademark of American National Standards Institute. NEC is a registered trademark of, and National Electrical Code (NEC) standard is a copyright of the National Fire Protection Association, Inc. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent 's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2021 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

