

PVC Conduit Cutters

Small Cutter



For fast, smooth field cuts of 1/2" through 1" Flex-Plus® Blue ENT.

Part No.	Size	Std. Ctn. Qty.
CC120B	8"	10

Medium Cutter



Hand held cutter makes fast square, smooth field cuts on conduit, sizes 1/2" through 1 1/4". Produces burr-free cut with no shavings. Fits into pocket or pouch.

Part No.	Size	Std. Ctn. Qty.
CC125	9"	12

Large Cutter



For clean cuts of conduit, sizes 1/2" through 2".

Part No.	Size	Std. Ctn. Qty.
CC122	17 1/2"	1

Tape



Prelubricated, woven polyester tape made from low friction, high abrasion resistant yarns providing a low coefficient of friction. Tape is printed with sequential footage markings for accurate measurements.

Part. No.	Size	Tensile Strength	Reel Lengths
TL14505	1/2"	1250 lbs.	5,000 ft.
TL14510	1/2"	1250 lbs.	10,000 ft.
TL38203	5/8"	1800 lbs.	3,000 ft.
TL38265	5/8"	1800 lbs.	6,500 ft.
TL38210	5/8"	1800 lbs.	10,000 ft.

Other tapes are available. Consult your sales service location for additional information.

Cement

(MSDS sheets available at www.carlon.com)

All Weather – ENT Blue



ENT cement required for use with ENT and Rigid Nonmetallic Conduit fittings

Recommended pipe application and sizes	Set-up time (Evaporation Rate)	Recommended installation temperature	Lap Shear @ 73°F	Viscosity at 75° as manufactured
Required for use with Flex-Plus® Blue ENT (Electrical Nonmetallic Tubing), Riser-Gard®, P&C Flex®, and Carlon PVC fittings. Up through 6" diameter.	-5°-10°F 6-8 minutes 10°-30°F 4-5 minutes 30°-50°F 3-4 minutes 50°-70°F 1-2 minutes 70°-90°F 1/2-1 1/2 minutes	-5° to 100°F	2 hrs. 350 psi 16 hrs. 800 psi 72 hrs. 1,500 psi	400-700 cps

Part No	Size	Applicator	Description	Ctn. Qty.	Ctn. Wt. (lbs.)
VC9992	Quart	Dauber	All Weather "Quick-Set" Blue	12	29.0

Meets ASTM D-2564