



USA VISION SYSTEMS
Ultra Class Series
4U Rackmount NVR Server

CPU		Intel i7 Skylake
Memory (RAM)		16 GB DDR4
Hot Swap Bay		2/ 4/ 8/ 20
Video	Codec	MPEG4, MJPEG, H.264
	Input	32
Video Resolution		2560x1920 (5M), 2560x1600 (4M), 2048x1536 (3M), 1600x1200 (2M), 1280x960 (1.3M), 640x480 (VGA), 320x240 (CIF)
Backup Type		DVD±R, DVD±RW, CD-R/RW
Recovery DVD		Automatic System Rebuild
Alarm Inputs	Sensor Input	4*
	Alarm Output	4*
Connector	Ethernet	2 x RJ-45, 10/100/1000 Mbps
	VGA Output	2 (DVI, VGA, or HDMI)
	USB 2.0 (F + R)	2 Front + 4 Rear
	USB 3.0	2 Rear
Remote Access		TCP/IP, LAN, WAN, Internet, ISDN
Operating Temperature		0 to 45 °C (32 to 133 °F)
Humidity		0 to 80% RH (non condensing)
Dimensions (W x D x H)	2 and 20 Bays	19 x 26 x 7 inch
	4 and 8 Bays	19 x 21 x 7 inch
Raid (optional)		0, 1, 5, 6
Power Supply	2 Bays	380W
	4 and 8 Bays	
	20 Bays	1080W
Optional Products		GV-IO 12-In Card / GV-IO 12-Out Card / GV-IO Box 4 / GV-IO Box 8 / GV-IO Box 16 / GV-Data Capture Box Series / GV-Hub Box / GV-COM Box/ GV-DOM / GV-Joystick / GV-Remote / GV - Keyboard
Languages		English/ Spanish