

# 1500VA Battery Backup

Commercial Line-Interactive Rack/Tower UPS

0E-1500VASNM

**UltraTech**  
POWER PRODUCTS

## PRODUCT DESCRIPTION

A rack/tower UPS with line interactive topology, the UltraTech 0E-1500VASNM provides battery backup and surge protection for servers, network devices, and telecom installations without an active power factor correction (PFC) power supply. The 0E-1500VASNM uses Automatic Voltage Regulation (AVR) to correct minor power fluctuations without switching to battery power, which extends battery life, essential in locations with frequent power fluctuations.

## FEATURES

- Automatic Voltage Regulation (AVR)
- 1500VA / 900W Capacity
- Simulated Sine Wave Output
- 8 Surge + Battery Backup Grounded Outlets
- LCD Display
- 2U Rack/Tower Mountable Chassis
- USB, Serial, SNMP Communication
- Telephone, Network, Coaxial Data Line Protection
- PowerPanel® Business Software for Remote Monitoring and Management (Free Download)



## SPECIFICATIONS

PART #	0E-1500VASNM
UPC	840049307315
CAPACITY	1500VA / 900W
OUTPUT	120 VAC +/- 10%
CORD LENGTH	10 ft. (3.0m)
OUTLET TYPES	8 x NEMA 5-15R
RUNTIME (HALF/FULL)	18 minutes / 6 minutes
DIMENSIONS	17.25 x 3.5 x 15.75 in. (438 x 89 x 400mm)
WEIGHT	21.95 lbs. (48.4kg)
WARRANTY	3-year
CONNECTED EQUIPMENT GUARANTEE	\$300,000

## TYPICAL APPLICATIONS

- Workstations
- Corporate and Department Servers
- Network Devices
- Telecom Installations



# 1500VA Battery Backup

Commercial Line-Interactive Rack/Tower UPS

**UltraTech**  
POWER PRODUCTS



8 Battery + Surge Protected Outlets

Data Line Protection  
Telephone / Network / Coaxial

## ADDITIONAL SPECIFICATIONS

INPUT	Circuit Breaker	15A
	Cord Length	10 ft. (3.0m)
	Input Frequency Range	47 Hz-63 Hz
	Nominal Input Voltage	120 VAC
OUTPUT	Automatic Voltage Regulation	Single Boost
	On Battery Frequency	50-60 Hz +/- 1%
	On Battery Waveform	Simulated Sine Wave
	UPS Topology	Line Interactive
	Overload Protection	Internal Circuitry Limiting, Circuit Breaker Protected
BATTERY	Typical Transfer Time	4 ms
	Battery Quantity	4 / User-Replaceable
	Battery Size	12V / 7Ah
	Replacement Battery Cartridge	RB1270X4J
SURGE PROTECTION AND FILTERING	Typical Recharge Time	8 hours
	EMI / RFI Filtration	Yes
	Phone / Network Protection RJ11 / RJ45	1-In / 1-Out (Combo)
MANAGEMENT AND COMMUNICATIONS	Surge Suppression	1840 J
	Audible Alarms	Battery Mode / Low Battery Overload / Fault / Battery Missing
	LCD	Multifunction LCD
	SNMP / HTTP Remote Monitoring	Yes, with optional RMCARD205
	Software (Free Download)	PowerPanel® Business

# 1500VA Battery Backup

Commercial Line-Interactive Rack/Tower UPS



## ADDITIONAL SPECIFICATIONS (CONT.)

<b>PHYSICAL SPECIFICATIONS</b>	Color	Black
	Form Factor	Rack / Tower
	Material of Construction	Metal
	Rack Height	2U
<b>WEIGHTS AND DIMENSIONS</b>	Width/Height/Depth (in)	17.25 x 3.50 x 15.75 in.
	Width/Height/Depth (cm)	43.82 x 8.89 x 40.01cm
	Width/Height/Depth (mm)	438 x 89 x 400mm
	Weight (lb)	48.40 lbs.
	Weight (kg)	21.95kg
<b>ENVIRONMENTAL</b>	Operating Relative Humidity	0 - 95% (non-condensing)
	Operating Temperature	32-95°F (0-35°C)
	Storage Temperature	5-113°F (-15-45°C)
<b>CERTIFICATIONS</b>	Environmental	RoHS Compliant
	Safety	UL1778
<b>WARRANTY</b>	CEG Amount	\$300,000
	Product Warranty	3-Year Limited