

# PROXIMITY CREDENTIALS

## PROGRAMMABLE, ISO



ADI PRO's ISO proximity credentials deliver contactless access control paired with exceptional durability and flexibility. These credentials can be programmed to the widest variety of leading proximity card formats, providing a convenient access control solution of the highest quality.



## FEATURES

Universal compatibility with 125kHz proximity readers

Durable PVC or composite construction with passive design (no battery) for long-term use

Available with magstripe for additional capabilities

External numbers and custom artwork available for easy identification

Custom programming (26-40 bit format)

Quick lead times and fast delivery

3-Year Warranty

Minimum order 100.  
For orders over 500, confirm lead time with supplier.  
Please note that all custom credentials are non-returnable.

## Product Specifications

### Dimensions:

3.37" x 2.125" x 0.033" (8.56 x 5.4 x 0.084cm)

Weight: 0.212 oz. (6g)

Frequency: 125kHz

Operating Temp.: -50° to 160°F (-45° to 70°C)

### Materials and Features by Product #:

#### PVC

0E-9011MPN: Seq. matching, no slot

0E-9011MPH: Seq. matching, horizontal slot

0E-9011MPV: Seq. matching, vertical slot

#### PVC + Magstripe

0E-9031MPN: Seq. matching, no slot

0E-9031SPN: Seq. non-matching, no slot

0E-9031MPH: Seq. matching, horizontal slot

0E-9031MPV: Seq. matching, vertical slot

#### Composite

0E-9021MPN: Seq. matching, no slot

0E-9021SPN: Seq. non-matching, no slot

0E-9021MPH: Seq. matching, horizontal slot

0E-9021MPV: Seq. matching, vertical slot

#### Composite + Magstripe

0E-9041MPN: Seq. matching, no slot

For more information contact  
your ADI Sales person or visit  
[adiglobal.com/adiexclusivebrands](http://adiglobal.com/adiexclusivebrands)