Push Terminal MP Video Balun

Push Terminal to BNC

0E-VBPUSHTMP



PRODUCT DESCRIPTION

0E-VBPUSHTMP is a miniature, single-channel passive video balun that enables full motion megapixel video transmission over UTP up to 2,000', or 3,000' if used with an active receiver. Easy installation with push terminals and BNC connector. One pair per package.

FEATURES

- Push terminal to BNC
- Compatible with standard, HD or 4K resolution
- Full motion video transmission via UTP Cat 5/5e/6/6a/7/8
- Standard resolution: Up to 2,000' (600m) HD-TVI 720P/1080P: Up to 820' (250m)

AHD 720P: Up to 1,148' (350m)/1080P: Up to 650' (200m) HD-CVI 720P: Up to 1,000' (300m)/1080P: Up to 820' (250m)

AHD/HD-CVI/TVI 3MP/4MP/5MP: Up to 650' AHD/HD-CVI/TVI 4K/8MP: Up to 328' (100m)



- High transient protection
- No power required
- For indoor use only

SPECIFICATIONS

PART#	0E-VBPUSHTMP
UPC	840049300422
FREQUENCY RESPONSE	DC to 8MHz
CMRR	60dB
IMPEDANCE	BNC 75 Ω , terminal 100 Ω
ATTENUATION	0.5dB typical
OPERATING TEMPERATURE	14°F to 158°F (-10°C to 70°C)
DIMENSIONS (EACH W/ PIGTAIL) (L x W x H)	8.2" x 0.63" x 0.69" (208 x 16 x 18mm)
WEIGHT (EACH)	1 oz. (28g)







