



# 12-Outlet Vertical Power Strip, 120V, 15A, 15 ft. (4.57 m) Cord, 5-15P, 36 in.

MODEL NUMBER: PS3612











### **Highlights**

- 12 outlets
- Convenient and safe covered, on/off switch
- 15-amp circuit breaker
- 15-ft. cord
- 36" length

#### **Package Includes**

- PS3612
- Mounting hardware
- Instruction manual

#### **Features**

- Sturdy all-metal 36 inch corded strip format with 2.638 inch center-to-center outlet spacing
- Includes 12 NEMA 5-15R output receptacles
- Ideal for horizontal or vertical raceway style power distribution in office, workbench, industrial, networking and telecom applications
- · Lighted power switch with locking transparent cover prevents accidental shutoff
- 15 amp electrical capacity with circuit breaker
- 120V AC, 50/60Hz electrical compatibility

## **Specifications**

OVERVIEW		
UPC Code	037332011459	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	15A 120V	
Input Cord Gauge Type	14 gauge; SJT	
Voltage Compatibility (VAC)	120	
Input Plug Type	NEMA 5-15P	
Input Cord Length (ft.)	15	



Input Cord Length (m)	4.57	
Integrated Cord Clip	No	
ОИТРИТ		
Frequency Compatibility	50 / 60 Hz	
Output (Watts)	1800	
Output Receptacles	(12) 5-15R	
Circuit Breaker (amps)	15	
Transformer Accommodation	(6) Yes	
Right-Angle Outlets	No	
Outlet Spacing	2.638 in.	
USER INTERFACE, ALERTS & CON	ITROLS	
Switches	Lighted 2 position switch controls power to all outlets	
Locking Switch Cover	Transparent on/off switch cover prevents accidental turn-off	
PHYSICAL		
Color	Silver	
Antimicrobial Coating	No	
Color (AC Line Cord)	Black	
Form Factors Supported	Supports horizontal or vertical raceway style power distribution in office, workbench, industrial, networking and telecom applications	
Included Mounting Accessories	Includes mounting clips	
Integrated Keyhole Mounting Slots	No	
Material of Construction	Aluminum	
Outlets Measurement (Center to Center)	67mm	
Receptacle Color	Black	
Shipping Dimensions (hwd / cm)	100.33 x 8.38 x 5.08	
Shipping Dimensions (hwd / in.)	39.50 x 3.30 x 2.00	
Shipping Weight (kg)	1.74	
Shipping Weight (lbs.)	3.84	
Unit Dimensions (hwd / cm)	91.5 x 3.8 x 3.8	
Unit Dimensions (hwd / in.)	36 x 1.5 x 1.5	
Unit Weight (kg)	1.72	
Unit Weight (lbs.)	3.8	
STANDARDS & COMPLIANCE		



**Tripp Lite**1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

Canada	cUL	
UL1363 (Power Tap)	UL1363	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>