

**4933****S2 AMPLIFIER 6 PORTS****SIMPLEBUS 2**

The art. 4933 is a concentrator with 6 outputs for star distribution of the video signal which is only directed and amplified towards the riser branch involved in the communication. The art. 4933 regenerates and amplifies the video signal with two levels of gain independently over the 6 outputs to increase the operating distances. The riser outputs used must be programmed manually or via art. 1249B. Compatible with all Simplebus 2 functions and products. 115÷230 VAC power supply. Housed in a box with 8-DIN modules. Dimensions: 140x140x67 mm.



**4933**

## S2 AMPLIFIER 6 PORTS

### GENERAL FEATURES

Input connector	Terminal block
CE certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

### MAIN FEATURES

Height (mm)	140
Width (mm)	140
Depth (mm)	67
Operating temperature (°C)	5 ÷ 40
Operating humidity (RH max) (%)	25 ÷ 95
DIN rail mounted	Yes
DIN modules (no.) (n°)	8
Maximum current absorption (mA)	150

### GENERAL DATA

Type of finishing materials	Plastic
Product color	White

### COMPATIBILITY

Simplebus 2 audio/video system	Yes
--------------------------------	-----

### MOUNTING/INSTALLATION

Wall-mounted	Yes
--------------	-----

### AUDIO/VIDEO FEATURES

Audio/video system	Yes
--------------------	-----