

## CTAM110C2



**Article Number:** 151-31109

**Cable Tie Anchor Mount, 0.17" Hole Dia., 0.2" Max Tie Width, PA66, White, 100/pkg**



Download spec sheet

### Base Data

<b>Local Order Number</b>	CTAM110C2
<b>Type</b>	CTAM1
<b>Color</b>	White (WH)
<b>Features and Benefits</b>	<ul style="list-style-type: none"> <li>• 4-way entry allowing the cable tie to secure bundles running parallel or perpendicular.</li> <li>• Secures with a single screw providing quick installation.</li> </ul>
<b>Product Description</b>	HellermannTyton cable tie anchor mounts are designed with a 4-way entry allowing the cable tie to secure bundles running parallel or perpendicular. The mounts are installed quick and easy by securing a single screw.
<b>Short Description</b>	Cable Tie Anchor Mount, 0.17" Hole Dia., 0.2" Max Tie Width, PA66, White, 100/pkg

### Product Dimensions

<b>Length L (Imperial)</b>	0.8 "
<b>Length L (Metric)</b>	20.4 mm
<b>Fixation Method</b>	Screw Mounting and Rivet
<b>Width W (Imperial)</b>	0.4 "
<b>Width W (Metric)</b>	10.2 mm
<b>Cable Tie Width Max. (Imperial)</b>	0.2 "
<b>Cable Tie Width Max. (Metric)</b>	5.0 mm
<b>Height H (Imperial)</b>	0.2 "
<b>Height H (Metric)</b>	5.1 mm
<b>Height H2 (Imperial)</b>	0.06 "
<b>Height H2 (Metric)</b>	1.8 mm
<b>Mounting Hole Diameter D (Imperial)</b>	0.17 "
<b>Mounting Hole Diameter D (Metric)</b>	4.3 mm
<b>Mounting Hole Diameter D Max. (Metric)</b>	4.3 mm
<b>Mounting Hole Diameter D Min. (Metric)</b>	4.3 mm

### Logistics and Packaging

<b>Quantity Per</b>	bag
<b>Package Quantity (Metric)</b>	100 Pieces
<b>Carton Quantity</b>	15000
<b>Weight (Metric)</b>	2 kg

### Material and Specifications

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Flammability** UL94 V2

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

**ROHS Compliant** Yes

**Certification/Specification** UL

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** Yes