

USB-C Docking Station, (x2) HDMI + VGA, Thunderbolt 3, USB-A, PD Charging – 1080p @ 60 Hz, Silver

MODEL NUMBER: U442-DOCK12-S



Features

Highlights

- Transmits audio/video signals from sources supporting USB DisplayPort Alt Mode
- Delivers HD picture quality at resolutions up to 1920 x 1200 (including 1080p) @ 60 Hz
- Connect all three video ports at the same time
- USB-A port transfers data from thumb drives or printers at speeds up to 5 Gbps
- Powers and charges PD Charging-compliant devices, such as MacBooks and Chromebooks
- Easy installation with plug-and-play operation—no software required

Applications

- Play video from your laptop or PC on an HDMI display, such as an HDTV or projector
- Transfer files to and from a USB thumb drive or external hard drive
- Charge your notebook or laptop by connecting its wall charger to the USB-C PD Charging port
- Write a report using a USB keyboard with your tablet or Android smartphone

System Requirements

- Source device with USB-C or Thunderbolt 3 port that supports USB DisplayPort Alternate



Mode

- Display device with VGA, DVI* or HDMI input
- Not for use with Thunderbolt monitors

Package Includes

- U442-DOCK12-S USB-C Docking Station, HDMI, Thunderbolt 3, PD Charging, VGA – 1080p @ 60 Hz, Silver
- Owner's manual

Specifications

MODEL TEXT	
What Does This Product Do?	
OVERVIEW	
Over Current Protection	
INPUT	
Cable Length (ft.)	
Cable Length (m)	
Cable Length (in.)	
Built-In Cable Length (ft.)	
Built-In Cable Length (m)	
Built-In Cable Length (in.)	
Built-In Cable Length (cm)	
External Power Supply Input Specs (V / Hz / A)	
External Power Supply Output Specs (V / A)	
External Power Supply Cord Length (ft.)	
External Power Supply Cord Length (m.)	
Cable Length (cm)	



Product Length (in.)	
Product Length (cm.)	
Product Length (ft.)	
Product Length (m.)	
USER INTERFACE, ALERTS & CONTROLS	
LED Indicators	
PHYSICAL	
Unit Dimensions (hwd / in.)	
Unit Dimensions (hwd / cm)	
Unit Weight (lbs.)	
Material of Construction	
Color	Silver
Transmitter Unit Dimensions (hwd / in.)	
Transmitter Unit Dimensions (hwd / cm.)	
Receiver Unit Dimensions (hwd / in.)	
Receiver Unit Dimensions (hwd / cm.)	
Transmitter Unit Weight (lbs.)	
Transmitter Unit Weight (kg)	
Receiver Unit Weight (lbs.)	
Receiver Unit Weight (kg)	
ENVIRONMENTAL	
Operating Temperature Range	
Storage Temperature Range	
Relative Humidity	
Operating Elevation (ft.)	
Storage Elevation (ft.)	
BTUs	
Power Consumption (Watts)	
Operating Humidity Range	
Storage Humidity Range	
Power Provided to Connected Device(s)	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

COMMUNICATIONS	
Signal Range (ft.)	
CONNECTIONS	
Ports	
PORT EXPANSION	
Max Distance (Between any 2 Units)	
FEATURES & SPECIFICATIONS	
Max Supported Video Resolution	
Audio Specification	
Recommended Category Cable	
CERTIFICATIONS	
Certifications	Tested to

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>