



Introduction

The Atlona **AT-DISP-CTRL** is a compact display controller, designed for small meeting spaces and huddle rooms. The DISP-CTRL detects connection of a source device with an active signal, and then automatically sends a control command to power up a display. Similarly, when the device is disconnected, the DISP-CTRL delivers a command to power down the display. The DISP-CTRL can be configured to deliver pre-stored or user-programmed display control commands through TCP/IP, RS-232, IR, or CEC. Additionally, this controller includes EDID and HDCP management features, and can be powered locally or through Power over Ethernet (PoE). The DISP-CTRL is HDCP 2.2 compliant and supports 4K/UHD video @ 60 Hz with 4:4:4 chroma sampling, as well as HDMI data rates up to 18 Gbps.

Applications

- **Huddle rooms and open meeting spaces**
The DISP-CTRL provides a simple automation solution for BYOD connectivity in any gathering area with a display installed, but no other AV equipment.
- **AV system upgrades**
The DISP-CTRL is ideal as an easy problem-solver for existing or legacy AV installations to provide automatic display control capabilities, without the need for a dedicated control system.

Key Features

Simple, automated display control

- Automatically changes display power state based on HDMI device connection or disconnection. Control signals to display are transmitted via IP, RS-232, IR, or CEC.
- Enables display, volume control, and input selection. Avoids the need for a handheld remote control which may be misplaced or non-functional.

Programmable display control modes

- A display can be powered off after a specified period of inactivity (no video signal detected), or after a device has been disconnected.
- Adjustable lamp cooldown mode also available to avoid prematurely powering up a projector after shutdown.

4K/UHD capability @ 60 Hz with 4:4:4 chroma sampling, plus support for HDR formats

- Ideal for new and emerging 4K/UHD and HDR-capable sources and displays. Compatible with 4K HDR10 and Dolby® Vision™ @ 60 Hz.
- Fully supports video resolutions, audio formats, and color space formats in the HDMI 2.0b specification.

HDMI input and pass-through ports with locking terminals

- Ideal for Atlona LinkConnect™ cables with locking HDMI connectors.
- Ensures fully secure cable connections and failsafe image display.

Local or PoE (Power over Ethernet) powering

- Industry standard IEEE 802.3af PoE can be supplied by a network switch or PoE injector. A power supply is also included.
- PoE allows convenient installation at a table or any other location, without the need for local AC power.

Intuitive GUI-based configuration using integrated web server

- Offers menu-based configuration of device settings, display device driver selection, and the ability to program control commands.
- Comprehensive selection of display drivers from the Velocity™ Control System driver database.

Dual Ethernet ports and integrated network switch

- Allows connection to a display for IP control, plus a LAN or direct web GUI access.
- Built-in network switch simplifies system integration and operation.

Award-winning 10 year limited product warranty

- Ensures long-term product reliability and performance in commercial and residential systems.
- Specify, purchase, and install with confidence.

Specifications

Video	
HDMI Specification	HDMI 2.0 ⁽¹⁾ , HDCP 2.2
UHD/HD/SD	4096x2160 @ 60 ⁽²⁾ /30/25/24 Hz, 3840x2160 @ 60 ⁽²⁾ /30/25/24 Hz, 1080p @ 60/59.9/50/30/29.97/25/24/23.98 Hz, 1080i @ 60/59.94/50 Hz, 720p @ 60/59.94/50 Hz, 576p @ 50 Hz, 576i @ 50 Hz, 480p @ 60/59.96 Hz, 480i @ 60 Hz
VESA	2560x1600, 2048x1536, 1920x1200, 1680x1050, 1600x1200, 1440x900, 1400x1050, 1280x1024, 1280x800, 1366x768, 1360x768, 1152x864, 1024x768, 800x600, 640x480
Color Space	YUV, RGB
Chroma Subsampling	4:4:4, 4:2:2, 4:2:0
Color Depth	8-bit, 10-bit, 12-bit
HDR	HDR10, Hybrid-Log Gamma (HLG), and Dolby [®] Vision™ @ 60Hz

Audio	
Pass-Through Formats	PCM, Dolby [®] Digital, Dolby Digital Plus™, Dolby TrueHD, Dolby Atmos [®] , DTS [®] Digital Surround™, DTS-HD Master Audio™, and DTS:X [®]
Sample Rate	32 kHz, 44.1 kHz, 48 kHz, 88.2 kHz, 96 kHz, 176.4 kHz, 192 kHz
Bit Rate	24 Mbits/s max

Protocols	
Supported	HTTP, Telnet
Addressing	DHCP, static

Control	
RS-232	Device control and configuration; supports baud rates from 2400 to 115200
IP	Device control and configuration
IR	Device control and configuration
CEC	Device control and configuration

Connectors	
HDMI IN	1 - Type A, 19-pin female
HDMI OUT	1 - Type A, 19-pin female
LAN ⁽³⁾	2 - RJ45, 10/100/1000 Mbps
RS-232	1 - 3-pin captive screw (bidirectional)
IR OUT	1 - 3.5 mm, unbalanced 2-channel
DC 5V	1 - mini USB

Controls and Indicators	
IP MODE, RESET	2 - momentary, tact-type
PWR indicator	1 - LED, green
LINK indicator	1 - LED, yellow

Resolution / Distance	4K/UHD - Feet / Meters		1080p - Feet / Meters	
HDMI IN/OUT	15	5	30	10

Signal	
Maximum TMDS Clock	600 MHz

Power	
PoE	IEEE 802.3af
Total power consumption	5.3 W
External Power (optional)	5 V, 500 mA (USB)

Environmental	
Operating Temperature	+32 to +122 °F 0 to +50 °C
Storage Temperature	-4 to +140 °F -20 to +60 °C
Operating Humidity (RH)	20% to 95%, non-condensing

Chassis	
Dimensions (H x W x D)	1.02 in x 4.29 in x 3.50 in 26 mm x 109 mm x 89 mm
Weight	0.65 lbs 0.30 kg
Safety	CE, FCC, RoHS

- (1) UHDp60 only supports 4:2:0.
- (2) 18 Gbps supported for HDMI 2.0 output.
- (3) Maximum distance per hop 330 ft (100 m), depending upon network configuration.

Accessories

Description	SKU
LinkConnect HDMI to HDMI Cable	AT-LC-H2H-1M / 2M / 3M
LinkConnect Mini DisplayPort to HDMI Cable	AT-LC-MDP2H-1M / 2M / 3M

Drawings

