



## Overview

Lead time	Usually in Stock
-----------	------------------

## General

Provided equipment	Installation guide Rack Mounting brackets Safety guide
--------------------	--

## Physical

Cable length	6 ft (1.83 m)
Color	Black
Depth	2.01 in (5.1 cm)
Height	72.01 in (182.9 cm)
Net Weight	18.03 lb(US) (8.18 kg)
Maximum Width	2.20 in (5.6 cm)

## Input

Line Rated Current	24 A
Max line current	30 A
Communication port protocol	SNMP Redfish
Input current limits	30 A
Load Capacity	8600 VA
Input Frequency	50/60 Hz
Plug standard	NEMA L21-30P
Nominal Input Voltage	3 phase

## Output

Number of power socket outlets	21 C13/C15 3 C19/C21
--------------------------------	-------------------------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Conformance

Product certifications	CUL Listed FCC part 15 class A
Standards	ICES-003

## Environmental

Ambient air temperature for operation	23...140 °F (-5...60 °C)
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-13...149 °F (-25...65 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)

## Batteries & Runtime

Communication network type	10/100/1000BASE-T Wi-Fi (optional)
----------------------------	---------------------------------------

## Ordering and shipping details

Package weight(Lbs)	22.75 lb(US) (10.32 kg)
---------------------	-------------------------

## Packing Units

Package 1 Height	80.31 in (204 cm)
Package 1 width	6.50 in (16.5 cm)
Package 1 Length	4.88 in (12.4 cm)
Number of Units in Package 3	48

## Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------