



Network

Bullet

# QNO-6082R1

2MP IR Bullet Camera



## Key Features

- Maximum 2megapixel (1920 x 1080) resolution
- 0.03lux (Color), 0Lux (B/W, IR LED on)
- 3.2 ~ 10mm (3.1x) motorized varifocal lens
- Maximum 30fps@2MP all resolutions (H.265/H.264)
- H.265, H.264, MJPEG codec supported, Multiple streaming
- Motion detection, Tampering, Defocus detection
- Hallway view (90°/270°), LDC support
- Micro SD/SDHC/SDXC memory slot (Max. 128GB)
- IR viewable length 30m
- IP66, IK10, PoE/12VDC
- No-audio model

# QNO-6082R1

2MP IR Bullet Camera



## Specifications

| Video                     |  |
|---------------------------|--|
| Imaging Device            | 1/2.8" CMOS  |
| Resolution                | 1920x1080, 1280x960, 1280x720, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360  |
| Max. Framerate            | H.265/H.264: Max. 30fps/25fps(60Hz/50Hz)<br>MJPEG: Max. 15fps (@2MP Max. 4fps)   |
| Min. Illumination         | Color: 0.03Lux(F1.6, 1/30sec)<br>BW: 0Lux(IR LED on)   |
| Video Out                 | CVBS: 1.0 Vp-p / 75Ω composite, 720x480(N), 720x576(P) for installation  |
| Lens                      |  |
| Focal Length (Zoom Ratio) | 3.2~10mm(3.1x) motorized varifocal   |
| Max. Aperture Ratio       | F1.6(Wide)~F2.9(Tele)  |
| Angular Field of View     | H: 109°(Wide)~33°(Tele) / V: 58°(Wide)~18°(Tele) / D: 132°(Wide)~38°(Tele)   |
| Min. Object Distance      | 0.5m (1.64ft)  |
| Focus Control             | Simple focus   |
| Lens Type                 | DC auto iris   |
| Operational               |  |
| Camera Title              | Displayed up to 85 characters  |
| Day & Night               | Auto(ICR)  |
| Backlight Compensation    | BLC, WDR, SDR  |
| Wide Dynamic Range        | 120dB  |
| Digital Noise Reduction   | SSNR   |
| Motion Detection          | 4ea, polygonal zones   |
| Privacy Masking           | 6ea, rectangular zones   |
| Gain Control              | Low / Middle / High  |
| White Balance             | ATW / AWC / Manual / Indoor / Outdoor  |
| LDC                       | Support  |
| Electronic Shutter Speed  | Minimum / Maximum / Anti flicker (1/5~1/12,000sec)   |
| Video Rotation            | Flip, Mirror, Hallway view(90-/270-)   |
| Analytics                 | Motion detection, Tampering, Defocus detection, Virtual area(Intrusion/Enter/Exit), Virtual line(Crossing/Direction)   |
| Alarm I/O                 | Input 1ea / Output 1ea   |
| Alarm Triggers            | Analytics, Network disconnect, Alarm input   |
| Alarm Events              | File upload via FTP and e-mail<br>Notification via e-mail<br>SD/SDHC/SDXC or NAS recording at event triggers<br>Alarm output<br>Handover(PTZ preset, Send message by HTTP/HTTPS/TCP) |
| IR Viewable Length        | 30m(98.42ft)   |

|                                   |  |
|-----------------------------------|--|
| <b>Network</b>                    |  |
| Ethernet                          | RJ-45(10/100BASE-T)  |
| Video Compression                 | H.265/H.264: Main/High, MJPEG  |
| Smart Codec                       | WiseStream II  |
| Bitrate Control                   | H.264/H.265: CBR or VBR<br>MJPEG: VBR  |
| Streaming                         | Unicast(6 users) / Multicast<br>Multiple streaming(Up to 3 profiles)   |
| Protocol                          | IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP |
| Security                          | HTTPS(SSL) Login Authentication<br>Digest Login Authentication<br>IP Address Filtering<br>User access log<br>802.1X Authentication(EAP-TLS, EAP-LEAP)                              |
| Application Programming Interface | ONVIF Profile S/G/T<br>SUNAPI(HTTP API)<br>Wisenet open platform   |

|                  |  |
|------------------|--|
| <b>General</b>   |  |
| Webpage Language | English, Korean, Chinese, French, Italian, Spanish, German, Japanese, Russian, Portuguese, Czech, Polish, Turkish, Dutch |
| Edge Storage     | Micro SD/SDHC/SDXC 1slot 128GB   |
| Memory           | 512MB RAM, 256MB Flash   |

|                                       |  |
|---------------------------------------|--|
| <b>Environmental &amp; Electrical</b> |  |
| Operating Temperature / Humidity      | -30°C ~ +55°C(-22°F ~ +131°F) / 0~90% RH<br>* Start up should be done at above -20°C |
| Storage Temperature / Humidity        | -30°C ~ +60°C(-22°F ~ +140°F) / 0~90% RH   |
| Certification                         | IP66, IK10   |
| Input Voltage                         | PoE(IEEE802.3af, Class3), 12VDC  |
| Power Consumption                     | PoE: Max 7.40W, typical 5.40W<br>12VDC: Max 6.50W, typical 4.80W                     |

|                                   |  |
|-----------------------------------|--|
| <b>Mechanical</b>                 |  |
| Color / Material                  | Dark grey / Aluminum                       |
| Product Dimensions / Weight       | ø78.0x259.8mm(ø3.07x10.23"), 900g(1.98 lb) |
| Compatible Conduit hole / Gangbox | Single, Double, 4" Octagon                 |
| Backbox                           | SBO-100B1, SBO-147B                        |

|                                  |   |
|----------------------------------|---|
| <b>DORI (EN62676-4 standard)</b> |   |
| Detect (25PPM/ 8PPF)             | Wide: 27.4m(89.85ft) / Tele: 128.8m(422.56ft) |
| Observe (63PPM/ 19PPF)           | Wide: 11.0m(35.94ft) / Tele: 51.5m(169.02ft)  |
| Recognize (125PPM/ 38PPF)        | Wide: 5.5m(17.97ft) / Tele: 25.8m(84.51ft)    |
| Identify (250PPM/ 76PPF)         | Wide: 2.7m(8.99ft) / Tele: 12.9m(42.26ft)     |