

























## **5MP** H.265 MOTORIZED LENS BULLET NETWORK CAMERA

5MP H.265 MOTORIZED LENS BULLET NETWORK CAMERA


The AVYCON AVC-NPB51M50 camera is a 5MP H.265 Bullet Network Camera. This 5MP IP camera supports True Day and Night mode, PoE, up to 165ft. of Smart IR Illumination, and also incorporates an InfiniteStar sensor which allows viewing of video in the lowest of light environments, even in color. This camera includes a Motorized 5mm - 50mm Lens with Auto-focus capabilities that can be controlled through a NVR. The AVC-NPB51M50 features Alarm Input/Output connections, Audio Input/Output, a microSD slot (128GB max capacity), and is ONVIF compliant. Also standard with this series is Digital NR, ROI, HLC, True WDR, and BLC capabilities along with IP67 outdoor rating. Optional accessories for this camera include a Junction Box Mount. Includes a MicroSD memory card slot for standalone recording applications.


## **FUNCTIONS**


- · 5MP ( 2592 x 1944 ) @ 30fps
- · Max. Resolution: 2592 x 1944
- · Supports Smart H.265/H.264 Encoding
- · True Day & Night ICR
- · IP67 Ingress Protection
- · Up to 165 ft. IR Illumination
- · Motorized 5mm 50mm Lens
- · 3D DNR, True WDR, HLC, BLC and ROI Encoding
- · Supports Triple Streams
- · Supports Audio Input and Output
- · Supports Alarm Output and Input
- · Supports Remote Access with Windows, macOS, iOS and Android
- · Operating Temperature: -22°F 131°F
- · DC12V / PoE (802.3af)
- · Built-in MicroSD Card Slot
- · Built-in Reset Button
- · NDAA Compliant

### **DIMENSIONS**

Unit: inch (mm)







#### **OPTIONAL ACCESSORIES**



AVM-JB-BE-S1(-G) JUNCTION BOX (FIT VERSION)



AVM-JB-BE-L1(-G) JUNCTION BOX (WIDE VERSION)



AVM-CRM-A1 CORNER MOUNT



AVM-POM-A1 POLE MOUNT



AVA-MICSPKSRN AUDIBLE AND VISUAL ALARM DEVICE

# **SPECIFICATIONS**

CAMERA	
Image Sensor	1/5" Progressive Scan CMOS
Resolution	
Image Size	2592 x 1944
	Color: 0.05lux @ F1.2(AGC ON) BW: 0lux w IR ON
	1/20,000s ~ 1/5s
Slow Shutter	
	Up to 165ft. (50m)
	Motorized 5 - 50 mm
	Horizontal: 101 ~ 32°, Vertical: 71 ~ 23°, Diagonal: 129 ~ 40°
	120dB
VIDEO STREAM	- Louis
Max. Image Resolution	2592 x 1944 @ 30fps
	2592 x 1944, 1920 x 1080, 1280 x 720, 640 x 480, 320 x 240
	2592 × 1944, 1920 × 1080, 1280 × 720
	720P(1280x720), VGA(640x480), QVGA(320x240)
	VGA (640x480), GVGA (320x240)
Video Compression	
	11.207 11.207 128 Kbps ~ 8 Mbps (CBR / VBR Adjustable)
	50Hz; 25fps@5MP/4MP/3MP/960P/720P/VGA/QVGA, 60Hz; 30fps@5MP/4MP/3MP/2MP/960P/720P/VGA/QVGA
NETWORK	00 Hz. Expector 7 Hz. 7 Co. 7
	1 x RJ45 10M / 100M Ethernet Port
	ONVIF Profile S / G
	HTTP, HTTPs, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTP, TCP/IP, PPPoE, DHCP
	IP Address Filter; Complicated Password; Authenticated Username and Password
IMAGE	
	IR cut filter with auto switch (Dav/Night/Auto/Schedule)
True WDR	
	Tes (3D DNR)
Backlight Compensation (BLC)	
Motion Detection	
Gain Control	
	Auto/Manual/Indoor
	Add/Marting/IIIQU/
	Flip/Rotation
Sharpness	
Image Setting	
	Support for English and Korean
VIDEO ANALYTICS	Discontinu Continu
Supported Recorders	
	Micro SD slot, up to 256GB
	1 input, 1 output/ 1 input (RCA), 1 output (RCA)
Hardware Reset	
	PID,LCD,PD/VD
	Human Detection, Vehicle Detection
	Motion Detection, Sensor Alarm
GENERAL	
Angle Adjustment	
	DC 12V / PoE (802.3af)
Power Consumption	
Ingress Protection	
Weight	
	-22°~131° F (-30°~55° Celcius)
Dimensions	11.79" x 4.25" (299.5mm x 108.0mm)

Copyright © AVYCON. All rights reserved. Specifications and pricing are subject to change without notice.

phone: 949-752-7606 email: info@avycon.com social: @avycon\_aivo website: avycon.com