

ZK400

4K UHD high brightness laser projector









- 4K UHD resolution, HDR and HLG compatible
- Lights on viewing 4000 lumens for use in brighter environments
- Small form factor with quiet operation
- DuraCore laser technology 30,000 hours virtually maintenance-free operation



The ZK400 is a compact 4K UHD laser projector. Designed for maintenance-free, continuous operation it can be installed in almost any orientation. Its small and lightweight footprint, combined with 360-degree and portrait projection makes it easy to install.

This feature-packed projector is 4K and HDR compatible, has a built-in speaker and its DuracCore laser technology delivers up to 30,000 hours of virtually maintenance-free laser light source.

Specifications

Display/image Display technology DIPTM

Resolution UHD (3840x2160) Brightness 4,000 lumens Contrast ratio 2,000,000:1 16:9 Native aspect ratio Aspect ratio - compatible 4:3 Keystone correction -+/-30° horizontal Keystone correction - vertical +/-30° Has vertical auto keystone

correction

Displayable colours (millions) 1073.4

Horizontal scan rate 15.375 ~ 91.146 Khz Vertical scan rate 50 ~ 120HzHz

Uniformity 75%

0.84m ~ 7.62m (33" ~ 300") diagonal Screen size

Yes

Lamp info Light source type LASER life 30,000 hours

Optical 1.5:1 ~ 1.66:1 Throw ratio

Projection distance (m) 1.2m - 9.9m Zoom 1.1 Manual Zoom type

Focal length (mm) 15.84mm~17.44mm Lens shift Vertical: +/-0% Native offset 105%

Connectivity

Connections Inputs 3 x HDMI 2.0, 1 x USB-A

Outputs 1 x Audio 3.5mm, 1 x S/PDIF Control 1 x RS232, 1 x 12V trigger, 1 x 3D sync

General Noise level (typical) 27dB Noise level (max) 29dB

PC compatibility UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac

2D compatibility NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz

SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)

3D compatibility TBC

3D 3D ready

Security bar, Kensington Lock, Password protected interface Security

25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, OSD / display languages Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnamese

24/7 operation

Operating conditions 0°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max

humidity 80% Remote control Backlit home remote 785BTU/hour

Heat dissipation Speaker count Watts per speaker 10W

AC power cord In the box Remote control

2x AAA batteries Basic user manual

Input lag 4.00ms

Optional wireless models UHDCast Pro, QuickCast Bundle, QuickCast starter kit

Power

100V ~ 240V, 50-60Hz Power supply

Power consumption (standby) <0.5W Power consumption (min) 175W Power consumption (max) 230W

Weight and dimensions

Dimensions (W x D x H) mm 337 x 265 x 119.3 Gross weight 6.5 kg Net weight 4.8 kg





