

### CPoEKIR2D

### Planning Instructions



CPL3IR2D (1)



CPoE60W (1)




PLW162500 (1)



CDIMMER (1)



CIRDPC (1)



Installer can run the complete spool of #16/2 500' wire to power fixtures.



**DANGER:** Exposure to infrared can cause permanent eye injury. Avoid direct eye exposure. Use proper eye protection when setting up and operating this product.

Questions on your system design?  
Call CAST Lighting at 973-423-2303

Important: Follow all local electrical codes and requirements.

[www.cast-lighting.com](http://www.cast-lighting.com) • 973-423-2303

Patents Pending. © Copyright 2022, CAST Lighting LLC. Hawthorne, NJ. All rights reserved.

### Kit Contents

Please check that you received all of these components.

- ☐ (1) CAST Infrared Night Owl Gen 3 IR LED 25 Watt 2Circuit Field Tuneable Lights (CPL3IR2D)
- ☐ (1) CAST Perimeter PoE 60 Watt (CPoE60W)
- ☐ (40) CAST Perimeter 11" Stainless Steel Ties (CPSSTIE11)
- ☐ (2) CAST UV Black 11" Cable Ties, pkg of 100 (CTIES)
- ☐ (1) 500 Ft. Roll CAST #16/2 No-Ox Wire (PLW162500)
- ☐ (1) Hand-Held 20 Level IR Field Tunable Brightness Adjustment Meter (CDIMMER)
- ☐ (1) IR Fixture 3' Dimmer Pigtail Connector (CIRDPC)
- ☐ (96) 1/4" 3M Heat Shrink Film, 1" pcs (XCEWPS30014)
- ☐ (1) Wire Quick Connect Cable Gland Separation Tool (C1098)
- ☐ (1) Wire Crimping Tool #10 & Cutter (CCRIMPCUT)
- ☐ (2) End Wire Crimp Caps (XCEW30648)

### Notes:

1. Attach wire directly to inside of horizontal fence pipe at 7 o'clock orientation. Use cable ties every 18 inches.
2. Attach wire to +/- blue terminal block 30V DC 60 Watt tap.
3. Make sure terminal block connection is tight.
4. PoE power supply requires network switch that delivers 60 Watts or better power to the CPoE60W. Commonly referred to as a PoE++ switch.