

BROADBAND 3dB HYBRID

700 - 2700 MHz

BDA-HC3-W2

Product Features

- Guaranteed PIM Compliance
- Wide Frequency Band Covering 700-2700MHz
- Low Insertion Loss
- Low VSWR
- High Isolation
- Indoor/ Outdoor Using IP65
- Available with Type N, 7/16DIN or 4.3/10 Connectors



| Specification | Value |
|-----------------------|-------------------------|
| Coupling | 3 dB |
| Insertion Loss | ≤0.65 |
| Isolation | ≥23 |
| Freq | 700-2700MHz |
| VSWR | ≤1.25 |
| PIM Rating | -153dBc@2x43dBm |
| Power Rating | 300W (average Per Port) |
| Impedance | 50 ohm |
| Connector | N-female |
| Color | Red |
| Operating Temperature | -25°C to +75°C |
| Weight | 0.60 kg |

DOC HON-62076.04 • 10202020 - DMC
Fiplex is a registered trademark of Fiplex Communications, Inc.
Fiplex Communications, Inc. reserves the right to change specifications without prior notice.

Honeywell Business Solutions
715 Peachtree Street NE
Atlanta, GA 30308
www.honeywell.com

HON-62076.04 • 10202020
©2020 by Honeywell International Inc. All rights reserved.
Unauthorized use of this document is strictly prohibited.
This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.
Country of origin: U.S.A.

**THE
FUTURE
IS
WHAT
WE
MAKE IT**

Honeywell