



**SILENT  
KNIGHT**

by Honeywell

---

## **SKE-SRM Remote Microphone Module Installation Instructions**

---

The SKE-SRM is a supervised remote microphone assembly that can be added to the SKE-Series voice evacuation system.

### **Compatibility**

---

The SKE-SRM is compatible with the SKE-Series voice evacuation system.

### **Mounting**

---


It is important to protect the SKE-SRM control panel from water. To prevent water damage, the following conditions should be avoided when installing the units:

- Do not mount directly on exterior walls, especially masonry walls (condensation)
- Do not mount directly on exterior walls below grade (condensation)
- Protect from plumbing leaks
- Protect from splash caused by sprinkler inspection ports
- Do not mount in areas with humidity-generating equipment (such as dryers, production machinery)

When selecting a location to mount the SKE-SRM cabinet, the unit should be mounted where it will NOT be exposed to temperatures outside the range of 0°C-49°C (32°F-120°F) or humidity outside the range of 10%-85% at 30°C (86°F) noncondensing.

### **To mount the remote microphone cabinet:**

1. Remove the SKE-SRM from its packing container.
2. Unlock the cabinet and remove the cabinet door.
3. Unplug microphone from microphone connector. Place microphone in a safe location while completing cabinet installation.
4. Remove the cover plate by un-screwing the four cover plate screws. Set the screws aside for later use.
5. Remove the remote microphone chassis assembly by un-screwing the two chassis assembly screws. See Figure 1.



**Figure 1: Remote Microphone Chassis Assembly**

