



HFX-7000M

SINGLE-FAMILY KIT W/ QUADRA AND MINI HANDS-FREE SB



The HFX7000M is our NEW and improved entry level video intercom kit with all the perks of its predecessor along with an updated design and improved technology. The kit includes our NEW 4.3" MINI-HF monitor, along with a power supply & and our NEW Quadra door entry station. Expandable up to 4 door stations and 4 interior monitors.

AWARDS





HFX-7000M

SINGLE-FAMILY KIT W/ QUADRA AND MINI HANDS-FREE SB

PRODUCTS IN THE KIT



EX-DSME 2-WIRE QUADRA EXTERNAL UNIT

External Unit with new mechanical push button and call buttons featuring exclusive “Sensitive Touch” technology. Die-cast aluminum cover with a protection degree of IK08. Colour HD camera, 4 indicator LEDs for call sent, door open, audio active, system busy and white LED for illumination. Nameplate holder in versions with 1/2/4 buttons that are programmable. Wall-mounted installation. Expandable up to 4 Panels - Expansion part number EX-DSQE. Only compatible for HFX-7000M, HFX-7000MW, HFX-8000M and HFX-9000M.

GENERAL DATA

Wall-mounted

Yes

HARDWARE FEATURES

Clamps

LL RTE COM DO SE- SE+C NC NO

ENVIRONMENTAL AND COMPLIANCE FEATURES

Operating temperature (°F)

-13 ÷ 131



HFX-7000M

SINGLE-FAMILY KIT W/ QUADRA AND MINI HANDS-FREE SB



EX-7000H COLOUR HANDS-FREE MINI MONITOR, S2

Door-entry phone with electronic call function, conversation button on base, call volume control and privacy function, door open button and supplementary button or additional services. On this model it is not possible to add extra buttons or LEDs. Dimensions: 95 x 215 x 58 mm.

GENERAL DATA

| | |
|-----------------------------|---------------------------------|
| Height (inch) (in) | 6.3 |
| Width (inch) (in) | 4.53 |
| Depth (inch) (in) | 0.87 |
| Product weight (oz) (oz) | 17.64 |
| Product color | White RAL9003 |
| Type of finishing materials | ABS |
| Wall-mounted | Yes |
| Desk base-mounted | Yes, with a dedicated accessory |

COMPATIBLE SYSTEMS

| | |
|---|-----|
| Audio/video Simplebus 2 with power supply art. 4888CU | Yes |
| Audio/video Simplebus 2 with power supply art. 1210/1210A | Yes |
| Simplebus 2 audio/video kit with power supply art. 1209 | Yes |

DISPLAY

| | |
|---------------------|---------|
| Display size (") | 4.3 |
| Aspect Ratio | 16:9 |
| Resolution (pixels) | 480x272 |

AUDIO FEATURES

| | |
|-------------|--------------------------|
| Microphone | 6mm (Ø), Omnidirectional |
| Loudspeaker | 36mm (Ø), 40 Ohm, 1W |



HFX-7000M

SINGLE-FAMILY KIT W/ QUADRA AND MINI HANDS-FREE SB

AUDIO FEATURES

| | |
|--------------------------|-------------|
| Technologies implemented | Full-Duplex |
|--------------------------|-------------|

ELECTRICAL CHARACTERISTICS

| | |
|----------------------------|--|
| Type of power supply | Power supply from video door entry bus |
| Supply voltage | 22 ÷ 34 VDC (Bus) |
| Absorption in stand-by (W) | 0.05 |
| Maximum absorption (W) | 8.8 |

HARDWARE FEATURES

| | |
|--|--|
| Type of buttons | Capacitive |
| Service buttons | Lock-release, Answer, Silent (Privacy) |
| No. of programmable buttons for additional functions | 2 (5 with accessory art. 6734W) |
| Clamps | L L CFP1 CFP2 |
| Removable terminals | Yes |
| Number of inputs (n°) | 1 |

SETTINGS

| | |
|---------------------------|-----|
| Loudspeaker volume | Yes |
| Microphone volume | Yes |
| Ringtone volume | Yes |
| Screen brightness control | Yes |
| Screen contrast | Yes |
| Screen colour | Yes |

ENVIRONMENTAL AND COMPLIANCE FEATURES

| | |
|---------------------------------|----------|
| IP protection rating | IP30 |
| Operating temperature (°F) | 41 ÷ 104 |
| Operating humidity (RH max) (%) | 25 ÷ 75 |
| Environmental class | I |



HFX-7000M

SINGLE-FAMILY KIT W/ QUADRA AND MINI HANDS-FREE SB

ENVIRONMENTAL AND COMPLIANCE FEATURES

| | |
|-------------------|--|
| CE certifications | RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011) |
|-------------------|--|

GENERAL FEATURES

| | |
|-------------------------------|-----|
| Door opening on call (Doctor) | Yes |
| Door opener | Yes |
| Self Activation | Yes |
| CPS call | Yes |
| Intercom calls | Yes |
| Actuator control | Yes |
| Multiple address | Yes |
| Outside door call input | Yes |
| Sending alarm calls | Yes |
| Silent mode (Privacy) | Yes |
| Automatic answer (handsfree) | Yes |
| Door open signaling | Yes |
| Customisable ringtone | Yes |



HFX-7000M

SINGLE-FAMILY KIT W/ QUADRA AND MINI HANDS-FREE SB



1209/4 4 OUTPUT POWER SUPPLY FOR 2-WIRE VIDEO KIT

Power supply for 2-wires video kit, 4 monitor outputs.

MAIN FEATURES

| | |
|----------------------------|------------------------|
| Supply voltage | 110÷240 VAC / 50÷60 Hz |
| Output supply voltage | 33VDC |
| Max. current delivered (A) | 0.5 |
| Maximum inrush current (A) | 2 |
| Input connector | Terminal block |
| Applicable to DIN rail | Yes |
| Number of DIN modules (n°) | 6 |

HARDWARE SPECIFICATIONS

| | |
|--------------------------|------|
| Product weight (oz) (oz) | 0.02 |
|--------------------------|------|

GENERAL DATA

| | |
|---------------------------------|----------|
| Height (inch) (in) | 3.52 |
| Width (inch) (in) | 4.17 |
| Depth (inch) (in) | 2.44 |
| Type of finishing materials | ABS |
| Product color | White |
| Operating temperature (°F) | 41 ÷ 104 |
| Operating humidity (RH max) (%) | 25 ÷ 75 |

COMPATIBILITY

| | |
|--------------------------------|-----|
| Simplebus 2 audio/video system | Yes |
|--------------------------------|-----|

MOUNTING/INSTALLATION

| | |
|--------------|-----|
| Wall-mounted | Yes |
|--------------|-----|



HFX-7000M

SINGLE-FAMILY KIT W/ QUADRA AND MINI HANDS-FREE SB

ELECTRICAL SPECIFICATIONS

| | |
|-----------------------------|----|
| Max absorption (W) | 12 |
| Maximum power delivered (W) | 17 |

**HFX-7000M****SINGLE-FAMILY KIT W/ QUADRA AND MINI HANDS-FREE SB****ACCESSORIES****4793MC CORTEN FACEPLATE FOR QUADRA W/BUTTONS**

Corten color faceplate for Quadra entrance panel with mechanical buttons.

**4793MB BLACK FACEPLATE FOR QUADRA W/BUTTONS**

Black faceplate for Quadra entrance panel with mechanical buttons

**4793MA ALUMINIUM FACEPLATE FOR QUADRA W/BUTTONS**

Aluminium colour faceplate for Quadra entrance panel with mechanical buttons

**1217A LABEL SHEETS FOR QUADRA W/BUTTONS**

The kit contains 10 sheets of adhesive labels for nameplates (7 for nameplates with 1 button, 2 for nameplates with 2 buttons, 1 for nameplates with 4 buttons) for Quadra push-button panel with mechanical buttons.

**4791 Adapter plate for Quadra**

Plate allowing installation of the Quadra external unit in 1- and 2-module flush-mounted boxes by Comelit, Bticino and Urmet.
Dimensions 137x236 mm

**4792 RAIN SHIELD FOR QUADRA ENTRANCE PANEL**

Rain shield in painted aluminum for Quadra entrance panel, grey colour. Dimensions (W x H x D): 99 x 210 x 41 mm.

**HFX-7000M****SINGLE-FAMILY KIT W/ QUADRA AND MINI HANDS-FREE SB****ACCESSORIES****6732 DESK BASE FOR HANDSFREE MINI MONITOR**

Desk base for desktop conversion of Handsfree Mini monitor. Complete with 1x 2 metre cable with RJ45 connector to connect monitor terminals to the coupler or domestic series socket. Dimensions: 140x190x140mm.

**6720 Access. cables external passage for MINI HF. S2**

Wall support bracket for handsfree Mini monitor allowing thru-routing of external cables.

**1405 DIGITAL EXCHANGE 2 QUADRA INPUTS. S2**

Audio/video switching module for audio/video kit systems. For use in systems with a maximum of 2 entrances with Quadra series external unit. Power supply from bus line. Dimensions: 35x90x58mm (2 DIN modules).

**1235A NAMEPLATE LABEL PRINTING SOFTWARE**

Dedicated software for the creation and printing of nameplate and information labels for Ikall, Vandalcom, Quadra and 316 Analog entrance panels. Requires use of adhesive labels art.1217, 1218, 1219 or art.1220. This software is available to download free of charge from the Comelit website

**1409 MODULE FOR REMOTE CAMERAS. SIMPLEBUS 2**

Remote camera module for Simplebus 2 2-wire digital systems. Allows management of up to 3 colour cameras in cyclical sequence from door entry monitors using a dedicated button. 12 Vac or 20 Vdc power supply. Dimensions: 60x85x35 mm (4 DIN modules).

**HFX-7000M****SINGLE-FAMILY KIT W/ QUADRA AND MINI HANDS-FREE SB****ACCESSORIES****1229A ADDITIONAL RINGTONE ACCESSORY. S2**

Wall-mounted accessory for additional ringtone for direct connection to 2-wire bus. Allows ringtone selection and adjustment of ringtone volume with privacy function, equipped with dip switches for user code programming, floor door call input terminals and call repeat. Fitted with distribution terminal art. 1214/2C. Dimensions: 125x95x24mm.

**1209 SIMPLEBUS2 VIDEO KIT POWER SUPPLY UNIT**

33 VDC power supply unit with overload and short circuit protection devices. It has two separate continuous outputs: one to power the external unit and electric lock, and the other to power the monitor. Input voltage 110-240 VAC. Dimensions: 106x62x89mm (6 DIN modules).

**1256 ACTUATOR RELAY. SIMPLEBUS 1 AND 2**

Intelligent Simplebus device for controlling a relay on board (12÷24 VAC/VDC - 10A max). For use and programming of the function required, follow the indications given in the technical documentation. It can be used in Simplebus system. Power supply: 12 VAC or 20 VDC. Dimensions: 66X85X35mm (4 DIN modules). Line branch terminal art. 1214/2C in equipment.