



KR1010 is an advanced access control reader with 125kHz & 13.56MHz RFID technology, respectively. It's an ideal choice for high-security applications. They are attractively designed to withstand harsh environments - to operate outside (IP66) and to offer a high vandal proof resistance (IK10).

FEATURES:

- IK10 (vandal-proof)
- IP66 (waterproof, dust-proof)
- Metal Casing
- Operating Frequency: 125kHz & 13.56MHz
- Operating Temperature: -40°F to 140°F
- Wiegand Outputs 26 / 34 bits
- Reading Distance: 2 6 cm

SPECIFICATIONS

Operating Voltage9-24v dcOperating Current< 50mA</th>Card Frequency125KHz & 13.56MHzCard TypeEM Card, S50, S70Card Reading Distance2 - 6 cmDimensions (WxHxD)43.13 x 2 x .83 inchesWiegand Output26 / 34 bitsWeight of Device0.53 lbsWeight of Device w/ Packaging0.6 lbsProtection LevelIK10 & IP66Operating Temperature-40°F to 140°FOperating Humidity20% - 80%

ZKTeco USA

1600 Union Hill Rd. Alpharetta GA 30005

Phone: (862) 505 -2101 · sales@zktecousa.com · www.zktecousa.com

© Copyright 2020. ZKTeco Logo and ZKTeco USA Logo are registered trademarks of ZKTeco or related company. All other product and company names mentioned are used for identification purposes only and may be the trademarks of their respective owners. All specifications are subject to change without notice. All rights reserved.