



The C2G Performance Series Ultra Flexible High Speed HDMI Cable is perfect for connecting a wide variety of devices from computers to projectors and monitors, AV presentation furniture, or in-wall applications requiring high speed HDMI features and video resolutions up to 4k (4096 x 2160) at 60Hz — perfect for conference rooms, classrooms, churches, and other commercial installations.

This Ultra Flexible High Speed HDMI Cable was designed for installations in tight spaces and offers commercial grade connectors that feature compact overmolding for high density environments, integrated finger grips on the top, bottom, and sides, for easy insertion and removal, and the gripping connector shell has 2x greater port retention to keep your devices connected. The gold plated connectors on the cable allow for better shielding, increased electrical conductivity, and durability.

This Ultra Flexible High Speed HDMI Cable supports the updated library of Consumer Electronic Control (CEC) commands, allowing communication between devices connected through the HDMI ports. Lastly, this fully-functional, high bandwidth cable has been tested to perform at industry standards and is backed by a lifetime warranty.

Features & Benefits

Supports all HDMI 2.0 features including resolutions up to 4K (4096 x 2160) at 60hz 4:4:4, which means higher quality video for viewing your screen content

Integrated finger grips on the connectors for easy insertion and removal

Gold plated connectors for increased electrical conductivity and enhanced durability

Backed by a Lifetime Warranty for peace of mind

In-wall (CMG/FT4) rated jacket, so you can safely run the cable inside of a wall and have a clutter free, clean look

Gripping connector shell for 2x greater port retention

Supports CEC extensions for control of consumer electronics devices through a single control point

Specifications

General Info

Product Line	C2G	Color	Black
UPC Number	757120103738	Country Of Origin	China
Features	Gripping Connectors	Application Sector	Residential, Commercial
Type	Cable		

Dimensions

Cable Length	1 ft
--------------	------

Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Video Resolution	4K 60Hz, 4K 30Hz, 4K, 1080p
Bend Radius	48 mm	Cable Type	High Speed HDMI, Ultra-Flexible, Video
Jacket Rating	CMG (FT4) Rated	Data Transfer Rate	18 Gbps

Adapter Rear	HDMI Male	Adapter Front	HDMI Male
Operating Temperature	-20 C, 75 C	Storage Temperature	-10 C, 55 C
