

The HDMI HDBaseT + RS232 and IR over Cat Extender Single Gang Wall Plate Transmitter - 4K 60Hz allows a 4K HDMI source to be extended up to 130ft to a 4K display using a single Cat6a Ethernet cable. This transmitter is an ideal part of an HDBaseT solution where HDMI video and audio in conference rooms, classrooms, lecture halls, and many other installation needs are far beyond the length limitations of standard HDMI cabling.

This transmitter extends HDMI over a single Cat5e, Cat6, or Cat6a network patch cable. Extend 4K HDMI up to 115 feet and 1080p up to 230 feet using a Cat5e or Cat6 cable. For longer 4K distances, extend 4K HDMI up to 130 feet using a Cat6a cable.



This HDMI HDBaseT transmitter is HDCP 2.2 compliant, ensuring that the source and display connection is secure. Multi-channel audio formats are supported, including PCM 2.0/5.1/7.1, Dolby TrueHD, Dolby Atmos, DTS-HD Master Audio, and DTS:X. With one-way Power over Cable (PoC) support, the transmitter gets its power from the receiver, so no additional power adapter is required, allowing for greater installation flexibility. Advanced users can control RS232 pass-through.

This HDBaseT transmitter works with [C2G30015](#) and [C2G30016](#) receivers.

Note: Ensure a solid, reliable connection between the 4K HDMI HDBaseT Extender and critical equipment. We suggest using HDMI Cables with gripping connectors that provide greater port retention than standard HDMI connectors.

Note: Stranded Cat5e/6/6a patch cables may be used for HDMI extension applications up to 230ft. Shielded, solid conductor Cat6 or HDBaseT Certified Cat6a network cabling is recommended for applications where the category cable must be coiled, is run near other high-frequency signaling cables, or in high EMI/RFI environments. For best performance use an [HDBaseT Certified Cat6a Patch Cable](#).

Features & Benefits

Extend 4K at 60Hz (4:2:0) up to 130ft and 1080p at 60Hz up to 230ft with Cat 6a cable	Extend 4K at 60Hz (4:2:0) up to 115ft and 1080p at 60Hz up to 200ft with Cat 5e/6 cable
HDCP 2.2 compliant, to create a secure connection between the source and display	Supports multi-channel audio formats, including PCM 2.0/5.1/7.1, Dolby TrueHD, Dolby Atmos, DTS-HD Master Audio and DTS:X
Supports EDID from the HDMI out and connected receiver has EDID limitation function	Supports CEC pass-through, allowing central control to all HDMI compatible devices
One-way IR pass through from the TX to the connected RX	One-way Power over Cable (PoC), powered by the receiver
Supports RS232 pass-through via HDBT port	HDBaseT Chipset VS010, for simpler HDBaseT installations

Compatible Receivers: [C2G30015](#), [C2G30016](#), C2G31015 (Coming Soon)

Specifications

General Info

Product Line	C2G	Color	White
UPC Number	757120300212	Country Of Origin	China

Features	RS232	Application Sector	Commercial
----------	-------	--------------------	------------

Type	HDBaseT, Transmitter		
------	----------------------	--	--

Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

Technical Information

Video Resolution	4K 60Hz, 4K 30Hz, 4K, 1080p 60Hz, 1080p	Adapter Front	DC Power Plug, RJ45 Female, HDMI Female
------------------	---	---------------	---

Operating Temperature	0 C, 45 C	Storage Temperature	-20 C, 70 C
-----------------------	-----------	---------------------	-------------
