

The HDMI over Cat Extender Box Transmitter to Box Receiver - 4K 60Hz allows a 4K HDMI source to be extended up to 131ft to a 4K display using a single Cat6/6a Ethernet cable. This is an ideal solution where HDMI video and audio in conference rooms, classrooms, lecture halls, and many other installation needs are far beyond the length limitations of standard HDMI cabling.



This HDMI over Cat Extender is HDCP 2.2 compliant, making sure that the connection from the source is secure. Multi-channel audio formats are supported, including PCM 7.1, Dolby TrueHD and DTS-HD Master Audio. With bi-directional Power over Cable (PoC) support, one power adapter at either transmitter or receiver side can power both units, so no additional power adapter is required, allowing for greater flexibility in installations.

**Note:** Ensure a solid, reliable connection between the 4K HDMI Extender and critical equipment. We suggest using HDMI Cables with gripping connectors that provide greater port retention than standard HDMI connectors.

## Features & Benefits

- Extend 4K at 60Hz (4:4:4) up to 115ft with Cat 6/6a cable
- Extend 4K at 30Hz (4:4:4) up to 131ft and 1080p at 60Hz up to 164ft with Cat 5e/6/6a cable
- HDCP 2.2 compliant, to create a secure connection between the source and display
- Supports multi-channel audio formats, including PCM 7.1, Dolby TrueHD and DTS-HD Master Audio
- Supports one-way IR pass-through from receiver to transmitter
- Supports bi-directional Power over Cable (PoC), one power adapter at either transmitter or receiver side can power both units
- Slim profile for easy installation

## Specifications

### General Info

Product Line	C2G	Color	Black
UPC Number	757120602200	Country Of Origin	China
Application Sector	Residential, Commercial	Type	Receiver

### Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

---

## Technical Information

---

Video Resolution	4K 60Hz, 4K 30Hz, 4K, 1080p	Adapter Rear	HDMI Female, RJ45 Female, DC Power Plug
Adapter Front	HDMI Female, RJ45 Female, DC Power Plug	Operating Temperature	0 C, 45 C
Storage Temperature	-20 C, 70 C		

---