



This precision-engineered cable is fully compliant with the DVI standard defined by DDWG (Digital Display Working Group). The DVI-I dual link configuration provides enough bandwidth for resolutions up to 2560 x 1600. Three analog 30 AWG coaxial lines enable high speed analog transmission.

Tri-shielded undermold and braid shield protects against unwanted EMI/RFI interference. Each coax line is individually wrapped in foam-polyolefin insulation and overwrapped with a braided tinned copper shield. 28 AWG copper conductors are individually insulated in hard-density polypropylene to minimize crosstalk, and ensure high speed, error-free transmission. Gold-plated contacts provide full conductivity with no data loss. PC and Mac compatible cable supports hot-plugging of DVI display devices. PC-99 color-coded: white.

## Features & Benefits

24-pin cable supports digital and analog transmission

Perfect for connecting digital displays and projectors to a PC

Available in lengths up to 5m

## Specifications

### General Info

Product Line	C2G	Color	Black
UPC Number	757120269496	Country Of Origin	China
Application Sector	Residential, Commercial	Type	Cable

### Dimensions

Cable Length	9.8 ft
--------------	--------

### Additional Information

Prop 65 Warning Required	Yes	Prop 65 Warning Language	Cancer and Reproductive Harm
--------------------------	-----	--------------------------	------------------------------

### Technical Information

Jacket Material	PVC (Polyvinyl Chloride)	Wire Gauge	30 AWG
-----------------	--------------------------	------------	--------

---

Video Resolution	UXGA (1600x1200)	Cable Type	Video
Jacket Rating	Standard Non-Rated	Adapter Rear	DVI-I Dual Link Male
Adapter Front	DVI-I Dual Link Male		

---