

APC Smart-UPS RT 192V RM Battery Pack



SURT192RMXLBP3U

Ov	er	VI	e	W
----	----	----	---	---

Lead time Usually in Stock

Main

wain	
Main Input Voltage	208 V
Number of rack unit	3U
Number of cables	1.0
Battery type	Lead-acid battery
Provided equipment	Installation guide Rack mounting brackets User manual

Physical

Colour	Black
Height	5.12 in (13 cm)
Width	17.01 in (43.2 cm)
Depth	25.98 in (66 cm)
Net weight	200.42 lb(US) (90.91 kg)
Mounting mode	Rack-mounted
USB compatible	No

Conformance

Standards OSHPD

Environmental

Ambient air temperature for operation	32104 °F (040 °C)
Operating altitude	010000 ft
Relative humidity	095 % non-condensing
Ambient air temperature for storage	5113 °F (-1545 °C)
Storage altitude	050000 ft (0.0015240.00 m)
Storage Relative Humidity	095 % non-condensing

D	atta	rios	Q.	D.	ıntime
ъ.	211 <i>0</i>	PPI	~	RI	intime

Number of battery blocks per string	16
Number of battery free slots	0
Number of battery filled slots	4
Battery manufacturer	Panasonic
Device mounting	Stand alone battery stack
Battery voltage	192 V
Additional information	Replace all batteries in operation together (UPS internal and external batteries) all-at-once
Number of battery replacement quantity	2
Replacement battery	APCRBC140 ☐

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16.26 in (41.3 cm)
Package 1 Width	39.37 in (100 cm)
Package 1 Length	23.62 in (60 cm)
Package 1 Weight	223.46 lb(US) (101.36 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Take-back	Take-back program available

Contractual warranty

Warranty 2 years repair or replace, optional on-site warranties available, optional extended warranties available

Recommended replacement(s)