

Product data sheet

Specifications



Rack PDU, Basic, Half Height, 200-208V, 30A, (14) C13, (2) C19

AP6002A

Overview

Lead time Usually in Stock

Main

Main Input Voltage 208 V

PDU Type Basic

Main Output Voltage 200 V
208 V

Input Connection Type NEMA L6-30P

Number of rack unit 0U

Cable length 10 ft (3.05 m)

Provided Equipment Installation guide
Safety guide

Physical

Color Black

Height 32.80 in (83.3 cm)

Width 2.20 in (5.6 cm)

Depth 1.85 in (4.7 cm)

Product Weight 6.13 lb(US) (2.78 kg)

Mounting Location Side

Mounting preference Lower

Mounting Mode Not rack-mountable

Mounting position Vertical

Input

Line Rated Current 24 A

Acceptable Input Voltage 200...240 V

Max line current 30 A

Input current limits 30 A

Load Capacity 5000 VA

Input Frequency 50/60 Hz

Output

Number of power socket outlets	14 IEC 60320 C13 2 IEC 60320 C19
--------------------------------	-------------------------------------

Conformance

Product Certifications	cUL Listed UL Listed
------------------------	-------------------------

Environmental

Ambient Air Temperature for Operation	32...122 °F (0...50 °C)
Relative Humidity	5...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...149 °F (-15...65 °C)
Storage Relative Humidity	5...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)

Ordering and shipping details

GTIN	731304327639
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	38.03 in (96.6 cm)
Package 1 Width	5.39 in (13.7 cm)
Package 1 Length	6.14 in (15.6 cm)
Package 1 Weight	7.14 lb(US) (3.24 kg)
SCC14	10731304327636

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Lead free	Yes
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Recommended replacement(s)