

Product data sheet

Specifications



APC Back-UPS 850VA, 120V, 2 USB charging ports, 9 NEMA outlets (3 surge)

BE850G2

Product availability : Stock - Normally stocked in distribution facility

Overview

Lead time Usually in Stock

Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Kw Rating	450 W
Rated power in VA	850 VA
Input Connection Type	NEMA 5-15P
Output connection type	6 NEMA 5-15R 3 NEMA 5-15R surge
Cable length	5 ft (1.52 m)
Number of cables	1
Battery Type	Lead-Acid battery
Provided equipment	User Manual USB cable

General

Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Color	Black
Height	5.47 in (13.9 cm)
Width	12.87 in (32.7 cm)
Depth	4.13 in (10.5 cm)
Net Weight	9.04 lb(US) (4.1 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable
Two post mountable	0

USB compatible	No
----------------	----

Input

Input Frequency	50/60 Hz +/- 3 Hz auto-sensing
Efficiency at full load	92...139 V

Output

Max Configurable Power (Watts)	450 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Topology	Standby
Waveform Type	Stepped approximation to a sinewave
Maximum configurable power in VA	850 VA
Transfer Time	6ms typical : 10ms maximum


Conformance

Product Certifications	California (CEC) Battery Charger cTUVus
Equipment protection policy	Lifetime : \$75000

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	10...90 %
Storage altitude	0...50000 ft (0.00...15240.00 m)
Acoustic level	45 dBA
Heat dissipation	19.249 Btu/h

Batteries & Runtime

Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	8 h
Battery Charge Power (Watts)	13 W rated
Battery power in VAH	102 VAh capacity 104 VAh runtime
Battery life	2...5 year(s)
Replacement battery	RBC17 
Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several variables including battery age, battery charge level, environmental conditions and characteristics of the connected load.
Extendable Run Time	0

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
-------	--

Surge Protection and Filtering

Surge energy rating 354 J

Ordering and shipping details

Category 11309-APC RESALE PRODUCTS

Discount Schedule APC1

GTIN 731304413592

Returnability No

Country of origin PH

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 7.72 in (19.6 cm)

Package 1 Width 6.61 in (16.8 cm)

Package 1 Length 16.38 in (41.6 cm)

Package 1 Weight 9.70 lb(US) (4.4 kg)

SCC14 10731304413599

Pallet layers 16

Offer Sustainability

EU RoHS Directive Under investigation

WEEE The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty 3 years repair or replace

Recommended replacement(s)