

# Product data sheet

Specifications



## APC Back-UPS Pro, 1350VA/810W, Tower, 120V, 10x NEMA 5-15R outlets, Sine Wave, AVR, USB Type A + C ports, LCD, User Replaceable Battery

BR1350MS

**Product availability : Stock - Normally stocked in distribution facility**

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	120 V
Kw Rating	810 W
Rated power in VA	1350 VA
Output connection type	6 NEMA 5-15R 4 NEMA 5-15R surge
Cable length	6 ft (1.83 m)
Number of cables	1
Battery Type	Lead-Acid battery

### General

Provided equipment	Coaxial cable User Manual USB cable
Product web sub-family	Gaming performance
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

### Physical

Height	10.24 in (26 cm)
Width	3.94 in (10 cm)
Depth	14.49 in (36.8 cm)
Net Weight	25.79 lb(US) (11.7 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable

Two post mountable	0
USB compatible	No

## Input

Input Frequency	60 Hz +/- 3 Hz
Efficiency at full load	88...147 V
Maximum Input Current per Phase	12 A
Switching current capacity	15 A

## Output

Max Configurable Power (Watts)	810 W
Output frequency	60 Hz +/- 3 Hz sync to mains
Topology	Line Interactive
Waveform Type	Sine wave
Maximum configurable power in VA	1350 VA
Transfer Time	8ms typical : 10 ms maximum


## Conformance

Product Certifications	ENERGY STAR V2.0 (USA) NOM TUV C-US certified
Equipment protection policy	Lifetime : \$500000

## Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...104 °F (-15...40 °C)
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...10000 ft (0.00...3048.00 m)
Acoustic level	45 dBA

## Batteries & Runtime

Included Battery Modules	1
Battery Slots Empty	0
Typical recharge time	16 h
RBC Quantity	2
Battery Charge Power (Watts)	10 W rated
Battery power in VAH	168 VAh capacity 168 VAh runtime
Battery life	3...5 year(s)
Replacement battery	<a href="#">APCRBC161</a> 
Extendable Run Time	0

## Communications & Management

Control panel Multi-function LCD status and control console

## Surge Protection and Filtering

Surge energy rating 1080 J

Filtering Full time multi-pole noise filtering :5% of IEEE surge let-through : zero clamping response time: in

## Ordering and shipping details

Category 11309-APC RESALE PRODUCTS

Discount Schedule APC1

GTIN 00731304335399

Returnability No

Country of origin PH

## Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 14.12 in (35.87 cm)

Package 1 Width 18.98 in (48.2 cm)

Package 1 Length 8.78 in (22.3 cm)

Package 1 Weight 29.32 lb(US) (13.3 kg)

SCC14 10731304335396

## Offer Sustainability

California proposition 65 WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

ENERGY STAR® [ENERGY STAR UPS V2.0 \(USA\)](#) [↗](#)

REACH Regulation [REACH Declaration](#)

EU RoHS Directive Compliant  
[EU RoHS Declaration](#)

Mercury free Yes

RoHS exemption information [Yes](#)

Optimized Energy Efficiency Energy efficient product

Take-back Take-back program available

## Contractual warranty

Warranty 3 years repair or replace

## Recommended replacement(s)