

# Product data sheet

Specifications

## APC Smart-UPS 1.5kVA 120V RM SHIPBOARD



SMT1500RMX93

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Rated power in W	1000 W
Rated power in VA	1440 VA
Input Connection Type	NEMA 5-15P
Output connection type	6 NEMA 5-15R
Number of cables	1
Battery Type	Lead-Acid battery
Provided equipment	User Manual

### Batteries & Runtime

Extendable Run Time	0
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	3 h
RBC Quantity	1
Battery life	3...5 year(s)
Battery power in VAh	432 VAh runtime
Battery Charge Power (Watts)	15 W rated

### General

Product web sub-family TAA compliance

### Physical

Height	3.39 in (86 mm)
Width	17.01 in (432 mm)
Depth	18.78 in (477 mm)

<b>Product Weight</b>	58.42 lb(US) (26.5 kg)
<b>Mounting Location</b>	Front
<b>Mounting preference</b>	No preference
<b>Mounting Mode</b>	Rack-mounted
<b>Two post mountable</b>	0
<b>USB compatible</b>	Yes

## Input

<b>Efficiency at full load</b>	82...144 V 120 V
<b>Input Frequency</b>	50/60 Hz +/- 3 Hz

## Output

<b>Harmonic distortion</b>	Less than 5%
<b>Maximum configurable power in VA</b>	1440 VA
<b>Max Configurable Power (Watts)</b>	1000 W
<b>Transfer Time</b>	6ms typical : 10ms maximum
<b>Topology</b>	Line Interactive
<b>Waveform Type</b>	Sine wave
<b>Full load runtime</b>	00:07:00
<b>Half load runtime</b>	00:26:00
<b>Output Frequency (sync to mains)</b>	50/60 Hz +/- 3 Hz for 60 Hz nominal sync to mains

## Conformance

<b>Product Certifications</b>	CSA C22.2 No 107.1
<b>Marking</b>	UL

## Environmental

<b>Acoustic level</b>	45 dBA
<b>Online Thermal Dissipation</b>	225 Btu/h
<b>Operating altitude</b>	0...9842.52 ft (0...3000 m)
<b>Ambient Air Temperature for Operation</b>	32...104 °F (0...40 °C)
<b>Ambient Air Temperature for Storage</b>	-4...131 °F (-20...55 °C)
<b>Storage altitude</b>	0.00...49212.60 ft (0...15000 m)
<b>Relative Humidity</b>	0...95 %
<b>Storage Relative Humidity</b>	0...95 %

## Communications & Management

<b>Audible Alarm</b>	Alarm on 25 alarm conditions
<b>Control panel</b>	LED status display with load and battery bar-graphs and On Line : On Battery : Replace Battery : and Overload Indicators
<b>Free slots</b>	0

## Surge Protection and Filtering

Surge energy rating	693 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m

## Ordering and shipping details

GTIN	731304433651
------	--------------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.25 in (23.5 cm)
Package 1 Width	24.02 in (61 cm)
Package 1 Length	23.23 in (59 cm)
Package 1 Weight	58.42 lb(US) (26.5 kg)

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

## Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---

## Recommended replacement(s)