



Fast, Simple, Clean
functional testing of smoke detectors

As market leaders with 30+ years' experience, we understand the need for reliable test solutions that keep up with technological developments – without compromising on the standards set by existing solutions.

Solo 365 is true to this belief – it's lighter to use, quicker to test, suitable for more applications and almost impossible to over-apply – eliminating the risk of detector contamination.

This new method of smoke generation takes Solo – the industry's most trusted brand – to the next level.

Solo 365 offers everything the industry expects from the Solo brand, pairing it with the very latest technology and wrapping it in a new modern slim-line design and incorporates non-hazardous, non-pressurized cartridges.

EVERY DAY USE

- Engineered for frequent, everyday use
- Compatible with Solo access poles
- User replaceable consumables (no service requirement)
- Compatible with the increasing number of sophisticated detectors now available
- Easier handling – 15% lighter than aerosol can and dispenser

SMOKE

- Eliminates risk of contamination
- Easy handling, storage & transportation
- Complies with latest regulations
- Controlled delivery via cartridges

KEY FEATURES

- Auto-start' – proximity sensor automatically initiates test
- 'Delayed start' mode - for non-standard detectors and ASD testing
- Flexible head – easy testing of hard-to-access detectors
- LED Auto-light – for testing in dark areas
- Clearing mode – for eliminating re-alarms

Use with SOLO ES6 Cartridges

Compact smoke detector testing cartridges for use with Solo 365. The Solo ES6 cartridge is non-hazardous and non-pressurized – allowing for easy storage and transportation.

- ✓ Detector manufacturer approved
- ✓ Rapid activation of detectors
- ✓ On demand smoke – less wastage and risk of contamination
- ✓ Cartridges sold in packs of 6



Product Features and Specifications

For use by specialized fire technicians



SOLO 365 Technical Information



Operating Features	<ul style="list-style-type: none"> • Color coded LED • Proximity sensor starts test • Suitable for detectors up to 110mm diameter • 5 seconds of stimulus, 5 seconds off repeat cycles
Safety Features	<ul style="list-style-type: none"> • Battery over current cut out • Over temperature cut out • 2-minute maximum duration time-out • Auto power after 10 minutes
Power Source	Lithium-Ion battery pack nominal 3.63V 9.5Wh, with USB charger connection
Battery Charging Time	Approximately 2 hours
Specifications	3lb, 20.5 x 9.25 x 5.25in

SOLO ES6 Technical Information



Operating Features	<ul style="list-style-type: none"> • Produces on-demand smoke • Rapid smoke detector activation
Safety Features	<ul style="list-style-type: none"> • Non-hazardous • Non-pressurized • Non-flammable
Power Source	N/A
Battery Charging Time	N/A
Specifications	1lb, 5.75 x 5.25 x 3.5in



Contact us
www.sdofire.com | sales@sdofire.com | 732-751-9266
 Route 66, Bldg. 6, Neptune, NJ 07753
 Connect with us @sdofire

