

# 440 Series

## Large Mushroom Button Switches

The conspicuous **440 heavy duty industrial series** switch assemblies incorporate a 2 $\frac{5}{8}$ " inch diameter mushroom button and heavy duty weather resistant contacts. The large double gang mushroom assembly includes a heavy duty steel bezel around the button to guard against abuse. When utilized as an exit or REX switch, the assembly is easy to activate and stands out for persons without prior knowledge of egress operation.

In addition to egress applications, the large assembly is ideal as an easy to activate emergency/panic alarm switch.



446U



442U



### MODELS

- 446** Momentary (MO), DPST
- 441** Alternate Action (AA) On/Off, DPST
- 442** Momentary (MO), DPST
- 444** Momentary (MO), DPST (2)

### STANDARD FEATURES

- 2 $\frac{5}{8}$ " mushroom exit switches
- Heavy duty to withstand impact
- Water resistant contacts
- Easy emergency/panic activation
- Ideal for high frequency use
- Screw terminal wire connections
- Red button standard


### OPTIONAL FEATURES


- Green button
- Visual status indicator (LED)
- Alternative signage




**SPECIFICATIONS**

	<b>446</b>	<b>441</b>	<b>442</b>	<b>443</b>	<b>444</b>
<b>Faceplate</b>	20 Gauge Stainless Steel	20 Gauge Stainless Steel	20 Gauge Stainless Steel	20 Gauge Stainless Steel	20 Gauge Stainless Steel
<b>Size</b>	Single Gang	Double Gang	Double Gang	Double Gang	Double Gang
<b>Dimensions</b>	2 <sup>7</sup> / <sub>8</sub> " x 4 <sup>1</sup> / <sub>2</sub> "	4 <sup>1</sup> / <sub>2</sub> " x 4 <sup>1</sup> / <sub>2</sub> "	4 <sup>1</sup> / <sub>2</sub> " x 4 <sup>1</sup> / <sub>2</sub> "	4 <sup>1</sup> / <sub>2</sub> " x 4 <sup>1</sup> / <sub>2</sub> "	4 <sup>1</sup> / <sub>2</sub> " x 4 <sup>1</sup> / <sub>2</sub> "
<b>Signage</b>	EXIT	-----	EXIT	EXIT	EXIT
<b>Wire Leads</b>	6" 20 AWG	6" 20 AWG	6" 20 AWG	6" 20 AWG	6" 20 AWG
<b>Button</b>	Red	Red	Red	Red	Red
<b>Weight</b>	0.5 lbs	0.5 lbs	0.5 lbs	0.5 lbs	0.5 lbs
<b>Input</b>	12/24 VDC ± 10%	12/24 VDC ± 10%	12/24 VDC ± 10%	12/24 VDC ± 10%	12/24 VDC ± 10%
<b>Contact</b>	DPST	DPST	DPST	SPST	DPST (2)
<b>Rating</b>	6 Amp @ 30 VDC Resistive	6 Amp @ 30 VDC Resistive	6 Amp @ 30 VDC Resistive	6 Amp @ 30 VDC Resistive	6 Amp @ 30 VDC Resistive
<b>Type</b>	Momentary (MO)	Alternate Action (AA) On/Off	Momentary (MO)	Momentary (MO) w/ External Relock Timer	Momentary (MO)

 Designates optional step

<p><b>1  SPECIFY MODEL</b></p> <p><b>SINGLE GANG</b></p> <p><b>446</b> Momentary (MO), DPST</p> <p><b>DOUBLE GANG</b></p> <p><b>441</b> Alternate Action (AA) On/Off, DPST</p> <p><b>442</b> Momentary (MO), DPST</p> <p><b>444</b> Momentary (MO), DPST (2)</p>		<p><b>SIGN</b></p> <p>EXIT</p> <p><b>SIGN</b></p> <p>[blank]</p> <p>EXIT</p> <p>EXIT</p>
<p><b>2  SPECIFY FINISHES</b></p> <p><b>U</b> 630 Dull Stainless  Standard</p> <p><b>S</b> 629 Bright Stainless</p> <p><b>C</b> 605 Bright Brass</p> <p><b>H</b> 613 Dark Oil Rubbed Bronze</p> <p><b>D</b> 606 Dull Brass</p> <p><b>Q</b> 626 Dull Chrome</p> <p><b>P</b> 625 Bright Chrome</p>	<p><b>3  SPECIFY OPTIONS</b></p> <p><b>G</b> Green Button</p> <p><b>L1G</b> Visual Status Indicator (LED), One Green</p> <p><b>L1R</b> Visual Status Indicator (LED), One Red</p> <p><b>L2</b> Visual Status Indicator (LED), One Green &amp; One Red</p> <p><b>LT</b> Visual Status Indicator (LED), One Tri-Color</p> <p><b>E*</b> Add "EXIT" Sign</p> <p><b>B**</b> No Sign, Blank</p> <p><small>* Available for 446 models only.</small></p> <p><small>** Available for 446, 442, 443 and 444 models only.</small></p>	

<b>STEP NUMBER:</b>	<b>1</b>	<b>2</b>	<b>3</b>
<b>ORDERING EXAMPLE:</b>	<b>446</b>	<b>U</b>	<b>LT</b>

 RELATED PRODUCTS

**RETROFIT BACK BOX**

**BB1D** Single Gang, 2 1/4" x 3 3/4" x 2 3/4"



