

7400

7400/7401 Ultraline Premium Electric Strike

Application:

The ULTRALINE 7400/7401 premium electric strike is designed for installation on aluminium single or double doors. The innovative and compact robust stainless steel split-jaw design maintains the high level of security expected from Adams Rite while enabling release electrically with over 15kg of sideload pressure.


Specification:

<ul style="list-style-type: none"> Monitoring option Opens electrically with over 15kg of sideload pressure Compact depth – 27mm overall 1080kg holding force Single solenoid operates at 12/24V DC Field selectable fail safe or fail secure on strike body 	<ul style="list-style-type: none"> Adjustable jaw Low current draw Retrofits all previous Adams Rite strikes Tested to 500,000 cycles Requires half the force to open compared with 7100, aiding compliance with Doc M requirements
--	--

Finish:

4710 Deadlatch ~ 4750 Deadlatch ~ Ritekey keypad ~ Push to Exit Button ~ Power Supply Unit

Standards:



Current Draw:	12v DC=0.44A, 24v DC intermitt. 0.23A continuous units are silent,
Voltage Tolerance:	+/- 10%
Powered by:	Internal solenoid
Monitoring:	(optional) Double latch and solenoid.
Duty:	Fail safe or fail secure selectable on strike body (supplied in fail secure mode) DC required for fail safe operation
Jaw Strength:	1080kg
Case:	85.6mm x 36mm x 27mm. Zinc aluminium alloy
Mechanism:	Stainless steel
Strike Opening:	36.5mm x 15.9mm (adjustable) x 12.7mm
Door gap:	Minimum 3mm, operational gap 3-5mm
Faceplate:	Flat and radius aluminium: 123.7mm x 31.8mm
Finishes [7400]:	628 Satin Anodised Aluminium (standard) 313 Dark Bronze Anodised Aluminium (option) 335 Black Anodised Aluminium (option) 630 Satin Stainless Steel (option)
Finishes [7401]:	130 to match 628 Satin Anodised Aluminium (standard) 121 to match 313 Dark Bronze Aluminium (option) 119 to match 335 Black Anodised Aluminium (option)
Subcover:	Standard subcover will suit a 44.45mm thick door that closes flush with jamb edge. For extension codes see below.
Standards:	ANSI/BHMA 156.5 Grade 1 UL listed for burglary resistance



7400

7400/7401 Ultraline Premium Electric Strike

Variants:

Code	Description
7400-628	ULTRALINE ELECTRIC STRIKE 12/24V DC FLAT SAA
7400M628	ULTRALINE ELECTRIC STRIKE 12/24V DC FLAT DOUBLE MONITORED
7401-130	ULTRALINE ELECTRIC STRIKE 12/24V DC RADIUS SAA
7401M130	ULTRALINE ELECTRIC STRIKE 12/24V DC RADIUS DOUBLE MON SAA