

EN

MS31

MICROWAVE TOUCHLESS ACTUATOR WITH ADJUSTABLE RANGE AND RELAY HOLD TIME



LEARN MORE



click or scan

TECHNOLOGY

CERTIFICATIONS







DESCRIPTION

BEA's **MAGIC SWITCH® Family** utilizes proven microwave motion technology to ensure consistent, dependable touchless activation and can be adjusted to comply with the ANSI 156.10 knowing act standard.

The **MS31** detects moving objects such as a hand, cart or wheelchair and reduces touchpoints in high traffic areas commonly found in shopping and transportation centers. Applications requiring hygienic activation include hospitals, pharmacies, clean rooms and foodservice facilities.



Adjustable Detection Zone

Detection zone from 4 to 24 inches (timed or toggle)

Adjustable LED Setting

Dipswitch position determines if LED illuminated when in detection or when not in detection

Silent Activation


Silent activation for hospitals and other noise-sensitive environments

Durable Design

IP54 rated enclosure for protection against outdoor weathering and daily cleaning

Various Faceplates Available

Available in black, gray and white faceplate; options include jamb style, single-gang, double-gang and 6 inch round



APPLICATIONS



Full Energy Swing Doors



Industrial Doors

TECHNICAL SPECIFICATIONS



Low Energy Swing Doors

Healthcare Environments

Technology Radiated Frequency Radiated Power Density	Microwave Doppler Radar 24.125 GHz < 5 mW / cm²
Detection Mode	Motion (bidirectional)
Detection Range	4 – 24" (adjustable)
Output Max. Contact Voltage Max. Contact Current Max. Switching Power	Relay with switch-over contact (voltage-free) 60 VDC / 125 VAC 1 A (resistive) 30 W (DC) / 60 VA (AC)
Output Hold Time	0.5 – 30 s
Supply Frequency	50 – 60 Hz
Supply Voltage	12 – 24 VAC ±10%, 12 – 24 VDC +30% / -10%
Power Consumption	< 1.5 W
Weight	0.34 lbs
Material	PC, PE
Temperature Range	-4 – 131 °F (-20 – 55 °C)
IP Rating	IP54
Dimensions Single Gang Jamb Plate Double Gang Round Plate	4 $\frac{1}{2}$ " (H) × 2 $\frac{3}{4}$ " (W) × $\frac{1}{4}$ " (T) 4 $\frac{1}{2}$ " (H) × 1 $\frac{3}{4}$ " (W) × $\frac{1}{4}$ " (T) 4 $\frac{1}{2}$ " (H) × 4 $\frac{1}{2}$ " (W) × $\frac{1}{4}$ " (T) 6" (D) × $\frac{1}{4}$ " (T)
Certification	EMC: 2004 / 108 / EC FCC: G9B-210161 IC: 4680A-210161

PRODUCT SERIES





10MS31U - B/G/W Black, gray or white, kit w/ Black, grav or white, kit single and double gang with jamb



10RD900 900 MHz Receiver





10TD900TR 900 MHz retrofit 10MS31R - B/G/W Black, gray or white, kit



DISCLAIMER Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will BEA be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information from this document or the products to which the information refers. BEA has the right without liability to change descriptions and specifications at any time.

WWW.BEASENSORS.COM



A Halma company