



Oneprox™ GS3 LF Mullion Reader

The PAC Oneprox™ GS3 LF Mullion reader has been designed to provide a smart solution for any access control application. The reader comes in a sleek, two-colour housing and with a light bar for visual indication. Its compact design makes the LF Mullion a perfect addition to any commercial application where flexibility and security are of paramount importance.

The Mullion reader is ideal for fitting on the frame of a door, internally or externally, and for fixing directly to most flush mounted electrical back boxes.

To make installations quick and easy the LF Mullion reader comes complete with a mounting bracket with fixing holes and a single screw to attach the reader. Additionally, the GS3 LF Mullion Reader also provides multiple output formats such as Wiegand 26, enabling connection to many third party access control platforms and with the integral tamper circuit it also meets EN 50131-1 & 3.

The Oneprox™ GS3 LF Mullion Reader's features and benefits:

- **Multiple outputs** - PAC, PAC64, Wiegand 26, Wiegand 34 and Wiegand Emulation mode to support many popular Wiegand formats
- **Versatile** - simple on-site configuration via the built-in switches to define supported card formats and both variable and fixed output formats. No need for programming cards or specific readers
- **Audiovisual identification** - lightbar (red/green) and audible sounder indicates valid/invalid card read, and tamper notification
- **Two Colour Housing** - fully encapsulated polycarbonate housing which meets IP65
- **Intruder Graded** - integral tamper circuit, meets EN 50131-1&3 for connecting to third party intruder panels
- **Confidence** - lifetime guarantee against electronic failure



Contact our dedicated customer services team on:

+44 (0) 161 406 3400

to find out how you can start benefiting from a tailored PAC security system that accommodates your business' requirements.

"The mounting bracket makes for a neater installation. Hiding the fixing screws when installing any reader has always been an issue, with the new mounting bracket everything is hidden making the installation neater."

Part number:
909020110 - PAC Oneprox™ GS3 LF Mullion Reader

Customer Support:

+44 (0) 161 406 3400

customerservices@stanleysecurityproducts.com

PAC Access Control, 1 Park Gate Close, Bredbury, Stockport, Cheshire, SK6 2SZ

www.stanleysecurityproducts.com



Oneprox™ LF Mullion Reader SPECIFICATIONS

Part Number	909020110 - PAC Oneprox™ GS3 LF Mullion Reader
Dimensions	
Weight	150g
PAC Credentials	21020 - PAC Token (with clip) 20204 - PAC Token (without clip) 21039 - PAC Card pk of 10 21087 - STANLEY Token 20250 - KeyPAC Token 21030 - KeyPAC Card
ID Technology	PAC, STANLEY, KeyPAC and Wiegand Prox
Programmable Output Formats	PAC, PAC64*, Wiegand & Magstripe
Maximum Read Range	Up to 85mm
Intruder Grading	Security Grade 3, Environmental Class 4A
Environment	IP65 - Indoor/ Outdoor weather resistant
Operating Voltage	12V to 24V DC
Maximum Current Requirements @12V DC	<100mA @ 12V DC
Operating Temperature	-40° to +66°C / -40° to +151°F
Operating Humidity	10 to 85% RH @ 30±2°C / 85±4°F
Audio Visual Indication	Bi-colour lightbar (red/green) and audible sounder
Tamper Output	Yes (dependent on controller specification), meets EN 50131-1 & 3
Material	Polycarbonate
Certification	CE compliant under the R&TTE Directive
Recommended Cabling Type	6 core 24 AWG alarm cable unscreened for PAC or 5-conductor 22AWG for Wiegand
Boxed Product Contents	Reader and instruction manual

* With PAC 512 or PAC 212 LF Controllers only

Ordering Information:

+44 (0) 161 406 3400

customerservices@stanleysecurityproducts.com

PAC Access Control, 1 Park Gate Close, Bredbury, Stockport, Cheshire, SK6 2SZ

www.stanleysecurityproducts.com

LFMULL/12.15