

## AOR-PSU-5-10 External Class 2 Power Supply for Fixed Station Analog Area of Rescue Systems

### Description

Model **AOR-PSU-5-10** is an external Class 2 power supply with enclosure for an AOR-5 or AOR-10 Command Unit.

### Features

- Class 2 power-limited output
- UL and cUL Listed (United States and Canada)
- Includes gray enclosure

### Specifications

Dimensions (W x D x H):	13.5 x 13.0 x 3.25 in. (342.9 x 330.2 x 82.6 mm)
Weight:	8.45 lbs. (3.83 kg)
Input:	Voltage: 115VAC Frequency: 60Hz AC Current: Maximum 3.5A Fuse Rating: 5A/250V
Output:	DC Voltage: 24VDC Rated Current: Maximum 2.5A (power-limited, continuous) Protection: Fused 3.5A
Supervision:	AC failure provides Form C contact
Operating Temperature:	+32° F to +120° F (0° C to +49° C)
Relative Humidity:	85% +/-5%
Approvals:	UL 294 (Access Control System Units) UL 603 (Power Supplies for Use with Burglar-Alarm Systems) UL 1069 (Hospital Signaling and Nurse Call Equipment) UL 1481 (Power Supplies for Fire-Protective Signaling Systems) CSA C22.2 No. 205 (Signal Equipment) CSA Standard C603-M1988 (Burglar Alarm System) California State Fire Marshall Approved
Warranty:	5-year limited warranty

