



IS407C Vandal-Resistant Apt. Intercom Station-Flush



ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The apartment station(s) shall be Alpha Communications® (V.I.P.™ series) model **IS407C** or approved equal. Station faceplate shall be minimum .035" solid stainless steel. Momentary action, metal push-buttons shall be provided for TALK, LISTEN and DOOR functions. Button markings shall be right on the faceplate. The speaker / microphone shall be a 2.75" (70mm) high-sensitivity type with excellent voice-frequency and tone signaling response. Color coded pigtailed shall be provided, and required wiring shall be only three (3) common wires and one (1) selective. (Add 1-common wire for systems with individual apt. door push-buttons that need to tone through the **IS407C** stations). Contractor shall observe all local and national electrical and building codes.

IS407C VANDAL-RESISTANT APARTMENT INTERCOM STATION

The Alpha Communications® **IS407C** (V.I.P.™ series) apartment intercom stations are designed specifically to minimize vandalism and tenant abuse. Made from .035" thick solid stainless steel, with solid metal push-buttons, these stations are made to last. A high sensitivity 2.75" (70mm) speaker assures clear voice communication, as well as tone signal response. The **IS407C** can be mounted flush on our popular **IH101** flush back box or **IH102** flush mounting ring. For surface mount requirements, use the **IH700G** surface box, or choose our model **IS407S** (surface) station instead.

Color-coded pigtail wiring makes these stations easy to wire and resists water corrosion found on P.C. board type stations. The advanced electronic design permits use in any size building.

A wide variety of optional accessories is available to provide additional functions such as multi-entrance operation, post office door release, silent or delayed door release, etc. Stations are also available in custom sizes and wiring configurations.

FEATURES

- Simple push button operation
- Made of Rugged Stainless Steel with Metal Push-Buttons
- Tamper and Vandal-Resistant
- Easy Installation
- Automatic Privacy
- Clear Voice Fidelity using high quality 2.75" voice speaker
- Simple to Operate and Reliable
- Requires only 3-common and 1-selective wire (add 1 common wire when apt. door tone signaling is required)

SPECIFICATIONS

Dimensions:	5.50"W (140mm) x 7.00"H (178mm) x 0.50"D (13mm) projection from wall (when flush mounted).
Construction:	Solid .035" thick Stainless Steel Faceplate.
Speaker / Mic:	2.75" (70mm) round, 45 ohms, designed for crystal-clear voice and tone signal response.
Push Buttons:	Individually replaceable Metal pushbuttons with self-wiping plated contacts. Identified TALK, LISTEN and DOOR.
Mounting:	Flush. Pre-punched mounting holes. Use with IH101 flush mounting box or IH102 flush mounting ring. Can also be surface mounted using IH700G surface box.

Alpha Communications

42 Central Drive • Farmingdale • NY • 11735-1202 • Phone: (631) 777-5500 • Fax: (631) 777-5599
TOLL-FREE: (800) 666-4800 • Web: www.alphacommunications.com • Email: info@alphacommunications.com

Copyright© 1998-2020 Alpha Communications® - All Rights Reserved.

Due to continuous product improvement, all colors, sizes, materials, finishes and specifications are subject to change without notice.