



RCB2400RN Refuge Call Box (AlphaRefuge™ 2400 Series)



Model **RCB2400RN**

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

The **AlphaRefuge™ 2400 Series** system Refuge Call Box(es) shall be Alpha Communications® **RCB2400RN**, or approved equal.

The **RCB2400RN** Refuge Call Box(es) shall be Surface Mount type and shall be enclosed in a Red fiberglass NEMA 4 rated enclosure, suitable for outdoor use. The **RCB2400RN** Refuge Call Box(es) shall contain a built-in heavy-duty metal call button and Red call placed / call answered LED.

The **RCB2400RN** Refuge Call Box(es) shall have power AND battery back-up power provided by the **PWRAPC** or **PWRAPC112** (depending on system capacity) central power supply and battery back-up unit.

The Refuge Call Box(es), shall be IBC, NFPA and ADAAG code compliant.

Contractor shall observe all local and national electrical and building codes.

RCB2400RN REFUGE CALL BOX (ALPHAREFUGE™ 2400 SERIES)



The Alpha Communications® **RCB2400RN** Refuge Call Boxes are used with the **AlphaRefuge™ 2400 Series** Area of Refuge system, and are Surface Mount type built into a NEMA rated fiberglass enclosure, suitable for outdoor use.

The **PWRAPC** or **PWRAPC112** (depending on system capacity) power supply unit can provide power and battery back-up for the **RCB2400RN** Refuge Call Boxes.

The **RCB2400RN** Refuge Call Boxes come standard with a built-in heavy-duty metal call button, and are available with an optional mushroom head call button (add Suffix- M).

The **RCB2400RN** Refuge Call Boxes come standard with a built-in Red call placed / call answered LED.

Only one (1) **PWRAPC** or **PWRAPC112** power supply is needed per system.

FEATURES

- Enclosed in a Red fiberglass NEMA 4 rated enclosure, suitable for outdoor use
- Fully Automated Operation
- Location Identification Message
- On-site Programming
- Heavy-duty Metal Call Button
- Call Placed / Call Answered LED
- IBC, NFPA, ADAAG Code Compliant
- Braille Label
- Options (at extra cost) Mushroom Head call button (add suffix- M) and built-in security pinhole camera
- Rated from -40 to +130 °F
- Made in USA

SPECIFICATIONS

| | |
|---------------------------|--|
| Dimensions: | 6.00"W (153mm) x 9.50"H (242mm) x 2.875"D (74mm) |
| Surface Enclosure: | Matching Red fiberglass NEMA 4 rated enclosure |

