



*Communication Systems*

---

6670 185<sup>th</sup> Ave NE \* Redmond, WA 98052 \* (425) 455-0510 \* (800) 692-0200

## **Wire Specification Sheet**

**Aiphone Part # 862208**

Description: 22 AWG 4 pair solid bare copper wire with FMPE insulation, shielded, with an overall PVC jacket for low-voltage electronic cable applications.

### **1. Conductor**

- 1.1. AWG Size & Stranding: 22 AWG Solid
- 1.2. Material: Annealed Bare Copper
- 1.3. Conductor Count: 4 Pair

### **2. Insulation**

- 2.1. Material: Foamed Polyethylene
- 2.2. Wall Thickness: 0.015"
- 2.3. Color Code: Red x Brown, Orange x Yellow, Green x Blue, Purple x Gray

### **3. Assembly**

- 3.1. Pair Lay Length: 1.50" LHL (8.00 Tw/Ft)
- 3.2. Cable Lay Length: 3.75" LHL (3.2 Tw/Ft)
- 3.3. Shield: Aluminum Mylar - 100% Coverage
- 3.4. Drain Wire: 24 AWG 7 Strand Tinned Copper

### **4. Jacket**

- 4.1. Material: Polyvinylchloride
- 4.2. Wall Thickness: 0.015"
- 4.3. Diameter: 0.251" ± .020"
- 4.4. Color: Gray
- 4.5. Ripcord: Yes
- 4.6. Weight: 31 Lbs/Mft

### **5. Markings\***

- 5.1. Type: Cable permanently identified via surface inkjet print
- 5.2. Legend: AIPHONE P/N 862208 E171202 22AWG 4PR SHIELDED  
75°C (UL) CL3 OR C(UL)US CM "ROHS COMPLIANT"  
MADE IN USA
- 5.3. Footage Markers: Yes

### **6. Electricals**

- 6.1. Impedance: 111 Ω ± 10%
- 6.2. Capacitance: 12.1 pF/ft.

6.3. DC Resistance: 16.1  $\Omega$ /Mft. @ 20° C

## 7. Standards

- 7.1. Cable suitable for installation under NEC (NFPA 70) articles 800, 725 & 760 guidelines
- 7.2. Cable suitable for installation in Canada under Section 60 of CEC, Part I
- 7.3. C(UL)US listed as CM per UL standard 444 and per CSA C22.2 No. 214-17
- 7.4. UL listed as CL3 per UL standard 13 and FPL per UL standard 1424
- 7.5. Cable is RoHS III complaint per Directive 2015/863/EU
- 7.6. Cable is REACH compliant per Regulation (EC) No 1907/2006 Updated July, 7 2017
- 7.7. Made in the USA

*ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION*

*ALL MEASUREMENTS ARE NOMINAL*