



FUNCTIONS

- · 5MP (2592 x 1944) @ 30fps
- · Max. Resolution: 2592 x 1944
- · Supports Smart H.265/H.264 Encoding
- · True Day & Night ICR
- · IP67 Ingress Protection
- · Up to 98 ft. IR Illumination
- · Motorized 2.7mm 13.5mm Lens
- · 3D DNR, True WDR, HLC, BLC and ROI Encoding
- · Supports Triple Streams
- · Supports Audio Input and Output
- · Supports Alarm Output and Input
- · Supports Remote Access with Windows, macOS, iOS and Android
- · Operating Temperature: -22°F 131°F
- · DC12V / PoE (802.3af)
- Built-in MicroSD Card Slot
- · Built-in Reset Button
- · NDAA Compliant

OPTIONAL ACCESSORIES



AVM-JB-BE-S1(-G)

JUNCTION BOX

(FIT VERSION)



AVM-JB-BE-L1(-G) JUNCTION BOX



AVM-CRM-A1 CORNER MOUNT



POLE MOUNT

AVM-POM-A1




AVA-MICSPKSRN AUDIBLE AND VISUAL ALARM DEVICE

5MP H.265 MOTORIZED LENS BULLET NETWORK CAMERA

5MP H.265 MOTORIZED LENS BULLET NETWORK CAMERA

The AVYCON AVC-NPB51M camera is a 5MP H.265 Bullet Network Camera. This 5MP IP camera supports True Day and Night mode, PoE, up to 98ft. of Smart IR Illumination, and also incorporates an InfiniteStar sensor which allows viewing of video in the lowest of light environments, even in color. This camera includes a Motorized 2.7mm - 13.5mm Lens with Auto focus capabilities that can be controlled through a NVR. The AVC-NPB51M features Alarm Input/Output connections, Audio Input/Output, a microSD slot (128GB max capacity), and is ONVIF compliant. Also standard with this series is Digital NR, ROI, HLC, True WDR, and BLC capabilities along with IP67 outdoor rating. Optional accessories for this camera include a Junction Box Mount. Includes a MicroSD memory card slot for standalone recording applications.

DIMENSIONS



Copyright © AVYCON. All rights reserved. Specifications and pricing are subject to change without notice.

SPECIFICATIONS

÷

CAMERA	
	1/2.7" Progressive Scan CMOS
Resolution	
	2592 x 1944
	Color: 0.05lux @ F1.2(AGC ON) BW: 0lux w IR ON
Shutter Speed	1/20.000s ~ 1/5s
Slow Shutter	
	Up to 98ft. (30m)
	Motorized 2.7 - 13.5 mm
	Horizontal: 101 ~ 32°, Vertical: 71 ~ 23°, Diagonal: 129 ~ 40°
	120dB
VIDEO STREAM	
Max. Image Resolution	2592 x 1944 @ 30fps
Supported Resolutions	2592 x 1944, 1920 x 1080, 1280 x 720, 640 x 480, 320 x 240
Main Stream	2592 x 1944, 1920 x 1080, 1280 x 720
Sub Stream	720P(1280x720), VGA(640x480), QVGA(320x240)
	VGA (640x480), QVGA (320x240)
Video Compression	
	128 Kbps ~ 8 Mbps (CBR / VBR Adjustable)
	50Hz: 25fps@5MP/4MP/3MP/2MP/960P/720P/VGA/QVGA, 60Hz: 30fps@5MP/4MP/3MP/2MP/960P/720P/VGA/QVGA
NETWORK	
	1 x RJ45 10M / 100M Ethernet Port
	ONVIF Profile S / G
	HTTP, HTTPs, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTP, TCP/IP, PPPoE, DHCP
	IP Address Filter; Complicated Password; Authenticated Username and Password
IMAGE	
	IR cut filter with auto switch (Day/Night/Auto/Schedule)
True WDR	
	Yes (3D DNR)
Backlight Compensation (BLC)	
Motion Detection	
Gain Control	
	Auto/Manual/Indoor
	Off/On (4 Zone, Rectangle)
	Flip/Rotation
Sharpness Image Setting	
	Support for English and Korean
VIDEO ANALYTICS	
Supported Recorders	Diversity Series
	Micro SD slot, up to 256GB 1 input, 1 output/ 1 input (RCA), 1 output (RCA)
Hardware Reset	
	PID.LCD.PD/VD
	Human Detection, Vehicle Detection
	Motion Detection, Sensor Alarm
GENERAL	
Angle Adjustment	Any Angle
	DC 12V / PoE (802.3af)
Power Consumption	
Ingress Protection	
Weight	
	-22°~131° F (-30°~55° Celcius)
	11.79" x 4.25" (299.5mm x 108.0mm)



Copyright © AVYCON. All rights reserved. Specifications and pricing are subject to change without notice.

phone: 949-752-7606 email: info@avycon.com social: @avycon_aivo website: avycon.com