


2413 Multi-Conductor - Enhanced Category 6 Nonbonded-Pair Cables



For more Information
please call

1-800-Belden1



General Description:

CAT6+ (350 MHz), 4-Pair, U/UTP-Unshielded, Plenum-CMP, Premise Horizontal Cable, 23 AWG Solid Bare Copper Conductors, Dual FRPO/FEP Insulation, Tape Separator, Ripcord, Flamarrest® Jacket

Usage (Overall)

Suitable Applications: Premise Horizontal Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155 ATM, 622 ATM, 250MHz Category 6

Physical Characteristics (Overall)

Conductor

AWG:

| # Pairs | AWG | Stranding | Conductor Material |
|---------|-----|-----------|--------------------|
| 4 | 23 | Solid | BC - Bare Copper |

Total Number of Conductors: 8

Insulation

Insulation Material:

| Insulation Material |
|--|
| FRPO/FEP - Flame Retardant Polyolefin/Fluorinated Ethylene Propylene |

Outer Shield

Outer Shield Material:

| Outer Shield Material |
|-----------------------|
| Unshielded |

Outer Jacket

Outer Jacket Material:

| Outer Jacket Trade Name | Outer Jacket Material |
|-------------------------|---------------------------------------|
| Flamarrest® | LS PVC - Low Smoke Polyvinyl Chloride |

Outer Jacket Diameter:

| Nom. Dia. (in.) |
|-----------------|
| 0.225 |

Outer Jacket Ripcord: Yes

Overall Cable

Overall Cabling Separator Material: Patented Dielectric Tape

Overall Nominal Diameter: 0.225 in.

Pair

Pair Color Code Chart:

| Number | Color |
|--------|------------------------------|
| 1 | White/Blue Stripe & Blue |
| 2 | White/Orange Stripe & Orange |
| 3 | White/Green Stripe & Green |
| 4 | White/Brown Stripe & Brown |

Mechanical Characteristics (Overall)

Storage Temperature Range: -20°C To +75°C

Installation Temperature Range: +5°C To +50°C

Operating Temperature Range: 0°C To +75°C

Bulk Cable Weight: 27 lbs/1000 ft.

Max. Recommended Pulling Tension: 40 lbs.

Min. Bend Radius/Minor Axis: 0.750 in.

Min. Bend/Installation: 2.250 in.

2413 Multi-Conductor - Enhanced Category 6 Nonbonded-Pair Cables

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

| | |
|---------------------------------------|-------------------------------------|
| NEC/(UL) Specification: | CMP |
| CEC/C(UL) Specification: | CMP |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| Other Standards: | ISO/IEC 11801 ed 2.1 (2008) Class E |
| EU CE Mark: | Yes |
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 10/13/2005 |
| EU Directive 2002/96/EC (WEEE): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |
| Telecommunications Standards: | Category 6 - TIA 568.C.2 |

Applicable Patents:

| |
|------------------|
| Country |
| www.belden.com/p |

Flame Test

| | |
|-------------------|---|
| UL Flame Test: | NFPA 262 Plenum Flame Test (UL910)(FT6) |
| C(UL) Flame Test: | FT6 |
| CSA Flame Test: | FT6 |

Suitability

| | |
|------------------------|-----|
| Suitability - Indoor: | Yes |
| Suitability - Outdoor: | No |

Plenum/Non-Plenum

| | |
|--------------------|------|
| Plenum (Y/N): | Yes |
| Non-Plenum Number: | 2412 |

Electrical Characteristics (Overall)

Nom. Mutual Capacitance:

| |
|---------------------|
| Capacitance (pF/ft) |
| 15 |

Maximum Capacitance Unbalance:

| |
|---------------------|
| Capacitance (pF/ft) |
| 330.000 |

| | |
|---|-----|
| Maximum Capacitance Unbalance (pF/100 m): | 330 |
|---|-----|

Nominal Velocity of Propagation:

| |
|--------|
| VP (%) |
| 72 |

Maximum Delay:

| |
|------------------|
| Delay (ns/100 m) |
| 537 @ 100MHz |

Max. Delay Skew:

| |
|-----------------------|
| Delay Skew (ns/100 m) |
| 35.000 |

Maximum Conductor DC Resistance:

| |
|------------------------|
| DCR @ 20°C (Ohm/100 m) |
| 7.800 |

Max. Operating Voltage - UL:

| |
|-----------|
| Voltage |
| 300 V RMS |

Maximum DCR Unbalanced:

| |
|--------------------------|
| DCR Unbalance @ 20°C (%) |
| 3.000 |

2413 Multi-Conductor - Enhanced Category 6 Nonbonded-Pair Cables

Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

| Freq. (MHz) | Max. Attenuation (dB/100 m) | Min. NEXT (dB) | Min. PSNEXT (dB) | Min. ACR (dB) | Min. PSACR (dB) | Min RL (dB) |
|-------------|-----------------------------|----------------|------------------|---------------|-----------------|-------------|
| 1 | 2.000 | 75.3 | 75.3 | 73.3 | 73.3 | 20.000 |
| 4 | 3.700 | 66.3 | 66.3 | 62.6 | 62.6 | 23.000 |
| 8 | 5.200 | 61.8 | 61.8 | 56.6 | 56.6 | 24.500 |
| 10 | 5.800 | 60.3 | 60.3 | 54.5 | 54.5 | 25.000 |
| 16 | 7.400 | 57.2 | 57.2 | 49.9 | 49.9 | 25.000 |
| 20 | 8.300 | 55.8 | 55.8 | 47.5 | 47.5 | 25.000 |
| 25 | 9.300 | 54.3 | 54.3 | 45.1 | 45.1 | 24.300 |
| 31.25 | 10.400 | 52.9 | 52.9 | 42.5 | 42.5 | 23.600 |
| 62.5 | 15.000 | 48.4 | 48.4 | 33.4 | 33.4 | 21.500 |
| 100 | 19.300 | 45.3 | 45.3 | 26.0 | 26.0 | 20.800 |
| 155 | 24.600 | 42.4 | 42.4 | 17.9 | 17.9 | 19.500 |
| 200 | 28.300 | 40.8 | 40.8 | 12.5 | 12.5 | 18.700 |
| 250 | 32.100 | 39.3 | 39.3 | 7.2 | 7.2 | 18.000 |
| 300 | 35.600 | 38.1 | 36.1 | 0.5 | 0.5 | 17.500 |
| 350 | 38.900 | 37.1 | 35.1 | -1.7 | -3.7 | 17.000 |
| 400 | 42.000 | 36.3 | 34.3 | -5.7 | -7.7 | 16.600 |
| 450 | 45.000 | 35.5 | 33.5 | -9.5 | -11.5 | 16.200 |
| 500 | 47.900 | 34.8 | 32.8 | -13.0 | -15.0 | 15.900 |
| 550 | 50.600 | 34.2 | 32.2 | -16.4 | -18.4 | 15.600 |

Premise Cable Electrical Table 2:

| Freq. (MHz) | Input (Unfitted) Imp. (Ohms) | Fitted Impedance | Min. ACRF (dB) | Min. PSACRF (dB) |
|-------------|------------------------------|------------------|----------------|------------------|
| 1 | 100 ± 15 | 100 ± 15 | 70.8 | 67.8 |
| 4 | 100 ± 15 | 100 ± 15 | 58.8 | 55.8 |
| 8 | 100 ± 15 | 100 ± 15 | 52.7 | 49.7 |
| 10 | 100 ± 15 | 100 ± 15 | 50.8 | 47.8 |
| 16 | 100 ± 15 | 100 ± 15 | 46.7 | 43.7 |
| 20 | 100 ± 15 | 100 ± 15 | 44.8 | 41.8 |
| 25 | 100 ± 15 | 100 ± 15 | 42.8 | 39.8 |
| 31.25 | 100 ± 15 | 100 ± 15 | 40.9 | 37.9 |
| 62.5 | 100 ± 15 | 100 ± 15 | 34.9 | 31.9 |
| 100 | 100 ± 15 | 100 ± 15 | 30.8 | 27.8 |
| 155 | 100 ± 22 | 100 ± 15 | 27.0 | 24.0 |
| 200 | 100 ± 22 | 100 ± 15 | 24.8 | 21.8 |
| 250 | 100 ± 32 | 100 ± 15 | 22.8 | 19.8 |
| 300 | 100 ± 32 | 100 ± 15 | 21.3 | 18.3 |
| 350 | 100 ± 32 | 100 ± 15 | 19.9 | 16.9 |
| 400 | 100 ± 32 | 100 ± 15 | 18.8 | 15.8 |
| 450 | 100 ± 32 | 100 ± 15 | 17.7 | 14.7 |
| 500 | 100 ± 32 | 100 ± 15 | 16.8 | 13.8 |
| 550 | 100 ± 32 | 100 ± 15 | 16.0 | 13.0 |

Notes (Overall)

Notes: Jacket sequentially marked at 2 ft./1m intervals. Third party verified to ANSI/TIA-568-C.2, Category 6. Values above 350 MHz are for Engineering Information Only.

Reference (Overall)

Previous Part Number: 24567415, 24567715, 24567736T, 24567615T, 25067545, 25067545T, 25067515T, 24567745T, 24567715T, 25067845, 25067845T, 25067836, 25067836T, 24567815, 24567815T, 2456705T, 24567145, 24567145T, 24567115, 24567115T, 24567345, 24567345T, 24567336, 24567336T, 24567315, 24567315T, 24567445T, 24567436, 24567436T, 24567415T, 24567A15T, 24567945, 24567945T, 24567936T, 24567915, 24567915T

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|---------------|----------|-------------|--------|-------|--------------------------|
| 2413 D15A1000 | 1,000 FT | 30.000 LB | BLUE | | CAT6+ 4PR U/UTP CMP RIB |
| 2413 D15U1000 | 1,000 FT | 28.000 LB | BLUE | | CAT6+ 4PR U/UTP CMP BOX |
| 2413 D151000 | 1,000 FT | 28.000 LB | BLUE | | CAT6+ 4PR U/UTP CMP REEL |
| 2413 D152500 | 2,500 FT | 65.000 LB | BLUE | | CAT6+ 4PR U/UTP CMP REEL |
| 2413 002A1000 | 1,000 FT | 30.000 LB | RED | | CAT6+ 4PR U/UTP CMP RIB |
| 2413 003A1000 | 1,000 FT | 30.000 LB | ORANGE | | CAT6+ 4PR U/UTP CMP RIB |
| 2413 003U1000 | 1,000 FT | 28.000 LB | ORANGE | | CAT6+ 4PR U/UTP CMP BOX |
| 2413 0031000 | 1,000 FT | 28.000 LB | ORANGE | | CAT6+ 4PR U/UTP CMP REEL |
| 2413 004A1000 | 1,000 FT | 30.000 LB | YELLOW | | CAT6+ 4PR U/UTP CMP RIB |
| 2413 004U1000 | 1,000 FT | 28.000 LB | YELLOW | | CAT6+ 4PR U/UTP CMP BOX |

2413 Multi-Conductor - Enhanced Category 6 Nonbonded-Pair Cables

| | | | | |
|---------------|----------|-----------|-------------|--------------------------|
| 2413 0041000 | 1,000 FT | 28.000 LB | YELLOW | CAT6+ 4PR U/UTP CMP REEL |
| 2413 0042500 | 2,500 FT | 65.000 LB | YELLOW | CAT6+ 4PR U/UTP CMP REEL |
| 2413 005A1000 | 1,000 FT | 30.000 LB | GREEN, DARK | CAT6+ 4PR U/UTP CMP RIB |
| 2413 005U1000 | 1,000 FT | 28.000 LB | GREEN, DARK | CAT6+ 4PR U/UTP CMP BOX |
| 2413 0051000 | 1,000 FT | 28.000 LB | GREEN, DARK | CAT6+ 4PR U/UTP CMP REEL |
| 2413 0052500 | 2,500 FT | 65.000 LB | GREEN, DARK | CAT6+ 4PR U/UTP CMP REEL |
| 2413 007A1000 | 1,000 FT | 30.000 LB | VIOLET | CAT6+ 4PR U/UTP CMP RIB |
| 2413 008A1000 | 1,000 FT | 30.000 LB | GRAY | CAT6+ 4PR U/UTP CMP RIB |
| 2413 008U1000 | 1,000 FT | 28.000 LB | GRAY | CAT6+ 4PR U/UTP CMP BOX |
| 2413 0081000 | 1,000 FT | 28.000 LB | GRAY | CAT6+ 4PR U/UTP CMP REEL |
| 2413 009A1000 | 1,000 FT | 30.000 LB | WHITE | CAT6+ 4PR U/UTP CMP RIB |
| 2413 009U1000 | 1,000 FT | 28.000 LB | WHITE | CAT6+ 4PR U/UTP CMP BOX |
| 2413 0091000 | 1,000 FT | 28.000 LB | WHITE | CAT6+ 4PR U/UTP CMP REEL |
| 2413 0092500 | 2,500 FT | 65.000 LB | WHITE | CAT6+ 4PR U/UTP CMP REEL |
| 2413 010A1000 | 1,000 FT | 30.000 LB | BLACK | CAT6+ 4PR U/UTP CMP RIB |
| 2413 010U1000 | 1,000 FT | 28.000 LB | BLACK | CAT6+ 4PR U/UTP CMP BOX |
| 2413 0101000 | 1,000 FT | 28.000 LB | BLACK | CAT6+ 4PR U/UTP CMP REEL |
| 2413 0102500 | 2,500 FT | 65.000 LB | BLACK | CAT6+ 4PR U/UTP CMP REEL |
| 2413 012A1000 | 1,000 FT | 30.000 LB | PINK | CAT6+ 4PR U/UTP CMP RIB |

Revision Number: 9 Revision Date: 02-27-2014

© 2014 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.