

The Installer's Choice



STAND-ALONE SYSTEM CHART



	C2R100/US	KCIEN	PROFIL 100 EC	GALEO	PROMI ECO	DG1	DGPROX	PROMI 1000 PC
Construction	Stainless Steel	Stainless Steel	Stainless Steel	ZAMAC (Zinc, Aluminium, Magnesium and Copper)	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate
Number of doors	1 door	1 door	1 door	1 door	1 door	2 doors	1 door	1 door (Manage by PC only)
Reading interface	Keypad	Keypad	Keypad	Keypad	Keypad	Keypad	Reader and Keypad	Reader and Keypad
User codes	150	100	100	100	100	500	500	1000
Electronics	Built-in Controller	Built-in Controller	Remote Controller	Remote Controller	Built-in Controller	Built-in Controller	Built-in Controller	Built-in Controller
Relays	2 Timed (1 to 99 sec.) or latched	2 Timed (1 to 99 sec.) or latched	1, 2 or 3 Timed (1 to 99 sec.) or latched	1, 2 or 3 Timed (1 to 99 sec.) or latched	1 Timed (1 to 99 sec.) or latched	2 Timed (1 to 99 sec.) or latched	1 Relay + 1 Alarm	1 NO / NC + 1 NO
REX input	1	1	1	1	1	2	1	1
Request-to-enter button	No	Yes	Yes	No	No	No	No	No
Alarm input	No	No	No	No	No	No	Yes	Yes
Back-Lit keys	Fluorescent keys	Yes	Yes	Yes	No	No	No	No
PIN digits	3 to 6 digits	4 to 6 digits	4 or 5 digits	4 or 5 digits	3 to 8 digits	5 digits	5 digits	5 digits
Remote Keypads/Readers Up to 50M (165ft)	N/A	N/A	N/A	N/A	N/A	KCP/BP	DGLI, DGLI/F, DGLP, DGLP/F, DGLIE, DGLP/60, DGLP/T	DGLI, DGLI/F, DGLP, DGLP/F, DGLIE, DGLP/60, DGLP/T
Tamper switch	Yes	Yes	No	No	No	No	Yes	Yes
Input voltage	10 to 26V AC/DC	12 - 24 VAC or 12 - 48 VDC	12 - 24 VAC or 12 - 48 VDC	12 - 24 VAC or 12 - 48 VDC	12 V AC/DC	12 V AC/DC	12 V AC/DC	12 V AC/DC
Factory reset	Keypad	Keypad and Jumper	Keypad and Jumper	Keypad and Jumper	Jumper	Jumper	Jumper	Jumper
Master code reset	Keypad	Jumper	Jumper	Jumper	Jumper	Jumper	Jumper	Software
Reset all user codes	Only by resetting to default	Only by resetting to default	Only by resetting to default	Only by resetting to default	Together with the master code	Together with the master code	Only by resetting to default	Deleting one or more cards through software
Operating temp.	-25°C to 55°C (-13°F to 131°F)	-25°C to 70°C (-13°F to 158°F)	-25°C to 70°C (-13°F to 158°F)	-25°C to 70°C (-13°F to 158°F)	-20°C to 70°C (-4°F to 158°F)	-30 to 70°C (-22°F to 158°F)	-30°C to 70°C (-22°F to 158°F)	-30°C to 70°C (-22°F to 158°F)
Weather proof	No	Yes	Yes	Yes	Yes	Yes	Yes	No

CDVI, DGI, DIGICODE, DMIK 36"x24" EN 03
CDVI reserves the right to change any of its products and specifications at any time without prior notice. Printed in Canada, June 2015