ELECTRIC STRIKES



LOCKING PRODUCTS

CX-EPD1289L: 3/4" 'UNIVERSAL' GRADE 1 FIRE RATED RIM STRIKE WITH PRELOAD

CX-EPD1289L Grade 1 electric RIM strike for pullman latches offers the best strike quality, with a preload release function for superior performance under the most demanding conditions. Industry-leading preload strike design registered under U.S. Patent 10,988,959. This award-winning strike is now available in a unique all-black finish, including the jaws and latch monitor.

Features

- Up to 15 lbs. of preload pressure
- · 'Universal' design, 12/24V, AC/DC
- 3/4" latch projection
- · 'Plug-in' latch bolt monitor assembly
- · 'No-cut' surface mount
- · Fail safe / fail secure

- · All-black finish available
- · Tamper resistant stainless steel construction
- Non-handed, with plug-in wiring harness
- · Stainless steel cover plate included
- · Metal mounting jig included
- 5 year warranty

	MODEL		
	CX-EPD1289L	Surface mount Grade 1 RIM strike with preload, 12/24V, AC/DC, fail safe/fail secure, c/w 'plug-in' latch monitor assembly and metal mounting jig	\$625.00
	CX-EPD1289L-BK	All-black finish, Surface mount Grade 1 RIM strike with preload, 12/24V, AC/DC, fail safe/fail secure, c/w 'plug-in' latch monitor assembly and metal mounting jig	\$645.00
	SPACER PLATE		
	CX-EPD1289-SPC	Spacer plate for CX-EPD1289L surface mount RIM strike	\$20.00









Specifications

Specificat	10113			
Voltage:	12/24V, AC/DC			
Current Draw:	560mA @ 12 VDC 280mA @ 24 VDC			
Strength - Static:	1,500 Lbs. Dynamic: 70 Ft- Lbs.			
Preload (Fail-Secur	reload (Fail-Secure Only): 15 Lbs.			
Endurance:	1,000,000 cycles (Factory Tested) 250,000 cycles (UL verified)			
Mode:	Fail-safe / Fail-secure			
Duty:	Continuous			
Fire Rating: UL10C	/CAN4-S104 3 hrs. (Fail Secure)			
Mechanical Adjustment: Strike Body				
Operation: AC-Buz	z, DC - Silent			
Latch Projection:	3/4"			
Latch Bolt Monitor	: SPDT, 100mA @ 24 VDC			
Dimensions (Body)	n: 9-1/8"H x 1-7/8"W x 3/4" D (231.6mm x 48mm x 19.8mm)			

Finally, a **RIM Strike Designed** for Every Installer!

CX-EPD1289L

Whether you've installed a hundred RIM strikes or just one, Camden's remarkable preload strike is designed to get you off the job faster and can even avoid future service calls!

The patented design of CX-EPD1289L RIM strikes will release with up to 15 lbs of preload pressure, caused by differences in air pressure, inexact installation, or misaligned doors (during or after installation).

