

**1998NV****AUDIO/VIDEO PORTER SWITCHBOARD. S1**

SIMPLEBUS1

Audio/video porter switchboard in desk version for Simplebus 1 system with microswitch keypad and 32-character alphanumeric display. Ergonomic handset with easier hangup, thanks to concealed magnetic panels. Allows the code and name of the called and calling users to be displayed, keeping unanswered calls stored in the memory. Manages Day/Night mode and user/user intercom service. Allows management of alarm indications originating from users. Up to 4000 users can be saved. Supplied with a removable cable with connection hub. 24 VAC power supply with art. 1195. Dimensions (L x H x D): 115x160x22 mm.

**AWARDS**DESIGN  
MILANO



**1998NV**

**AUDIO/VIDEO PORTER SWITCHBOARD. S1**

**COMPATIBLE SYSTEMS**

Audio/video Simplebus 2 with power supply art. 4888CU	Yes
---	-----

--	--

**DISPLAY**

Display type	Graphic LCD
--------------	-------------

Display size (")	3.5
------------------	-----

Resolution (pixel)	320x240
--------------------	---------

**ELECTRICAL CHARACTERISTICS**

Max/min absorption (mA)	30 ÷ 300
-------------------------	----------

Type of power supply	External power supply
----------------------	-----------------------

Maximum absorption (W)	5
------------------------	---

**HARDWARE FEATURES**

Number of push-buttons (n°)	28
-----------------------------	----

Number of outputs (n°)	2
------------------------	---

**SETTINGS**

Loudspeaker volume	Yes
--------------------	-----

Microphone volume	Yes
-------------------	-----

**ENVIRONMENTAL AND COMPLIANCE FEATURES**

Environmental class	III
---------------------	-----

**MAIN FUNCTIONS**

Door opener	Yes
-------------	-----

Self Activation	Yes
-----------------	-----

**GENERAL FEATURES**

Call type	Push-buttons
-----------	--------------



**1998NV**

## AUDIO/VIDEO PORTER SWITCHBOARD. S1

### GENERAL FEATURES

CE certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)
OSD display	Yes

### MAIN FEATURES

Height (inch) (in)	4.33
Depth (inch) (in)	8.86
Product weight (oz) (oz)	52.91
Operating temperature (°F) (°F)	23 ÷ 104
Operating humidity (RH max) (%)	25 ÷ 90
Maximum current absorption (mA)	300

### SOFTWARE/FIRMWARE SPECIFICATIONS

Number of user codes (n°)	4000
No. of storable users (n°)	4000

### GENERAL DATA

Type of finishing materials	ABS
-----------------------------	-----

### FUNCTIONS

Alarm function	Yes
Actuator control function	Yes
Intercom function	Yes
Key button function	Yes

### MOUNTING/INSTALLATION

Desk base-mounted	Yes
-------------------	-----

### CONNECTIVITY

Type of connections/ports	1xUSB 2.0, 1xRS232
---------------------------	--------------------