
TECH SHEET Expansion external unit kit **EX-BSB**External unit **EX-B**




The EX-BSB is the additional external unit kit for HFX-700B, HFX-700W, HFX-9500M Kits.

The EX-BSB is composed of:



MAXIMUM EXPANSION EXTERNAL UNITS FOR KITS HFX-700B, HFX-700W, HFX-9500M



SPECIFICATIONS ART. EX-B

GENERAL DATA

 Height
 5.90 in

 Width
 3.15 in

 Depth
 1.06 in

 Weight
 10.58 oz

 Wall-mounted
 Yes

CAMERA FEATURES

Sensor type 1/4" CMOS Lens optical dimensions 1.46 mm

Angle of view (H x V) 96° x 79° , 108° diagonal

Sensitivity 0.1 lux (color)
Video resolution (H x V) 640x480 pixels

ELECTRICAL CHARACTERISTICS

Type of power supply Power supply from bus

Supply voltage 33 VDC
Absorption in stand-by 1,2 W
Maximum absorption 10 W

HARDWARE FEATURES

Call type Push-button
Type of button Mechanical
Number of push-buttons 1 (1 user)

Type of outputs Door release (direct current output): unlock pulse of 4A, holding current of 200mA for 12VAC / DC locks (maximum

impedance 18 Ohm)

Door release (relay contact): C-NO, 10A@12÷24 VAC/VDC

SETTINGS

Loudspeaker volume control Yes
Microphone volume control Yes

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection rating IP54

Operating temperature $-13^{\circ}F \div 131^{\circ}F (-25^{\circ}C \div 55^{\circ}C)$

Operating humidity (RH max) $0 \div 95\%$

Environmental class IV (for use out of doors where the system components are fully exposed to the weather)

SPECIFICATIONS ART. 1405

DIMENSIONS

 Width
 1.42 in

 Height
 3.54 in

 Depth
 2.28 in

 Weight
 7 oz


ENVIROMENTAL

Operating Temperature 23° F/104°F (-5°C/+40°C)


ELECTRICAL SPECIFICATIONS

Power consumption 0,2W





1405 UNIT DIMENSIONS





CERTIFIED MANAGEMENT SYSTEMS







www.comelitgroup.com Via Don Arrigoni, 5 - 24020 Rovetta (BG) - Italy

