



FEATURES	DGLPFNWLC26	DGLPWLC26	DGLIFWLC26	DGLIWLC26	NANOPB	STARPB	SOLARPB	SOLARKPB
Casing Construction	Polycarbonate	Polycarbonate	Stainless Steel	Stainless Steel	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate
Card Reading Technology	125 Khz	125 Khz	125 Khz	125 Khz	125 Khz	125 Khz	125 Khz	125 Khz
Multi-card protocol (CDVI, HID and most popular 26-bit cards)	✓	✓	✓	✓	CDVI Cards Only	✓	✓	✓
Keypad & Reader	—	—	—	—	—	—	—	✓
Indoor/Outdoor (PCB sealed in epoxy)	✓	✓	✓	✓	✓	✓	✓	✓
Read Range (depends on type of card or tags)	Up to 3.5" (8 cm)	Up to 4" (10 cm)	Up to 2" (5 cm)	Up to 2" (5 cm)	Up to 2.4" (6 cm)	Up to 2.4" (6 cm)	Up to 2.4" (6 cm)	Up to 2.75" (7 cm)
Audible and Visual Feedback	✓	✓	✓	✓	✓	✓	✓	✓
Vandal Resistant	—	—	✓	✓	—	—	—	—
Backlit keys	—	—	—	—	—	—	—	—
Input voltage	12 Vdc	12 Vdc	12 Vdc	12 Vdc	12 Vdc	12 Vdc	12 Vdc	12 Vdc
Current Consumption	100 mA	100 mA	100 mA	100 mA	100 mA	100 mA	100 mA	150 mA
Tamper switch	—	—	—	—	—	—	—	—
Door contact & REX input	—	—	—	—	—	—	—	—
Lock output	—	—	—	—	—	—	—	—
Operating temperature	-22°F to 140°F (-30°C to 60°C)	-22°F to 140°F (-30°C to 60°C)	-22°F to 140°F (-30°C to 60°C)	-22°F to 140°F (-30°C to 60°C)	-22°F to 158°F (-30°C to 70°C)	-22°F to 158°F (-30°C to 70°C)	-22°F to 158°F (-30°C to 70°C)	-13°F to 158°F (-25°C to 70°C)
Dimensions	5.5" x 1.65" x .9" (140 x 42 x 23 mm)	4" x 3.15" x .9" (104 x 80,5 x 23 mm)	5.5" x 1.4" x .8" (140 x 35 x 2.5 mm)	4" x 3.15" x .9" (104 x 80,5 x 23 mm)	2.75" x 1.7" x .9" (70 x 43 x 23 mm)	5.1" x 1.6" x 1.1" (130 x 41 x 28 mm)	5.5" x 1.65" x 1.4" (140 x 42 x 23 mm)	5.5" x 1.65" x 1.4" (140 x 42 x 23 mm)
Certifications	RoHS, WEEE, IP53, CE FCC, R&TTE	RoHS, WEEE, IP53, CE FCC, R&TTE	RoHS, WEEE, IP53, CE FCC, R&TTE	RoHS, WEEE, IP53, CE FCC, R&TTE	RoHS, WEEE, IP53, CE FCC, R&TTE, ETL (UL294)	RoHS, WEEE, IP53, CE FCC, R&TTE, ETL (UL294)	RoHS, WEEE, IP53, CE FCC, R&TTE, ETL (UL294)	RoHS, WEEE, IP53, CE FCC, R&TTE



FEATURES	KCPROXWLC26	DGLP60WLC	DGLPMWLC	DGLIMWLC	STAR1M	SOLARMB	SOLARMBD
Casing Construction	Stainless Steel	Polycarbonate	Polycarbonate	Stainless Steel	Polycarbonate	Polycarbonate	Polycarbonate
Card Reading Technology	125 Khz	125 Khz	13.56Mhz Classic	13.56Mhz Classic	13.56Mhz Classic (Stand-Alone or Wiegand)	13.56Mhz Classic	13.56Mhz Classic & DesFire EV1
Multi-card protocol (CDVI, HID and most popular 26-bit cards)	✓	✓	—	—	—	—	—
Keypad & Reader	✓	—	—	—	—	—	—
Indoor/Outdoor (PCB sealed in epoxy)	✓	✓	✓	✓	✓	✓	✓
Read Range (depends on type of card or tags)	Up to 2" (5 cm)	Up to 23.5" (60 cm)	Up to 4" (10 cm)	Up to 2" (5 cm)	Up to 2.4" (6 cm)	Up to 3" (7.7 cm)	Up to 3" (7.7 cm)
Audible and Visual Feedback	✓	✓	✓	✓	✓	✓	✓
Vandal Resistant	✓	—	—	✓	—	—	—
Backlit keys	✓	—	—	—	—	—	—
Input voltage	12 Vdc	12 Vdc	12 Vdc	12 Vdc	12 Vdc	12 Vdc	12 Vdc
Current Consumption	120 mA	450 mA	100 mA	100 mA	200 mA	100 mA	220 mA
Tamper switch	—	—	—	—	—	—	—
Door contact & REX input	—	—	—	—	✓ REX (Relay)	—	—
Lock output	—	—	—	—	✓ (Relay)	—	—
Operating temperature	-13°F to 158°F (-25°C to 70°C)	-22°F to 140°F (-30°C to 60°C)	-13°F to 158°F (-25°C to 70°C)	-22°F to 158°F (-30°C to 70°C)	-22°F to 158°F (-30°C to 70°C)	-13°F to 158°F (-25°C to 70°C)	-13°F to 158°F (-25°C to 70°C)
Dimensions	7.5" x 1.7" x 1" (190 x 43 x 27 mm)	15.75" x 12.8" x 1" (400 x 325 x 25 mm)	4" x 3.15" x .9" (104 x 80,5 x 23 mm)	4" x 3.15" x .9" (104 x 80,5 x 23 mm)	5.1 x 1.6" x 1.1" (130 x 41 x 28 mm)	5.5" x 1.65" x 1.4" (140 x 42 x 23 mm)	5.5" x 1.65" x 1.4" (140 x 42 x 23 mm)
Certifications	RoHS, WEEE, IP53, CE FCC, R&TTE	RoHS, WEEE, IP53, CE FCC, R&TTE	RoHS, WEEE, IP53, CE FCC, R&TTE	RoHS, WEEE, IP53, CE FCC, R&TTE	RoHS, WEEE, IP53, CE FCC, R&TTE	RoHS, WEEE, IP53, CE FCC, R&TTE	RoHS, WEEE, IP53, CE FCC, R&TTE