

AL201UL

Access Control Power Supply/Charger

Altronix AL201UL single output Power Supply/Charger converts a low voltage input into a Class 2 Rated power-limited auto-resettable 12VDC output.



AL201UL

Specifications

Input

Voltage 24VAC, 40VA from
UL Listed, Class 2 transformer

Output

Class 2 Rated power-limited auto-resettable output
Voltage 12VDC
Current 1.75A supply current
Other Short circuit and thermal overload protection
Filtered and regulated

Back-up Battery *(not included)*

Type Sealed lead acid or gel type
Failover Upon AC loss, instantaneous

Supervision

AC Failure Form "C" contacts
Low Battery Form "C" contacts

Indicators (LED)

Input Input voltage is present
DC Output Powered

Agency Listings

UL UL294 (Access Control)
UL603 (Power Supplies for Use with
Burglar Alarm Systems)

Physical and Environmental

Dimensions (H x W x D)

Enclosure: 8.5" x 7.5" x 3.5" (215.9mm x 190.5mm x 88.9mm)
Shipping: 13" x 10" x 7" (330.2mm x 254mm x 177.8mm)

Weight (approx.)

Product: 4.25 lb. (1.93 kg)
Shipping: 4.75 lb. (2.15 kg)

Temperature

Operating: 0°C to 49°C (32°F to 120°F)
Storage: -20°C to 70°C (-4°F to 158°F)

Relative Humidity 85% +/- 5%

BTU/Hr. (approx.) 11 BTU/Hr.

Lifetime Warranty