

Part #: DX006

6 CHANNEL

D-Series Distribution Corrugated Steel Tape (CST) Armored Cables

Laser Ultra-Fox™ Fiber Performance

Industry Standard Designation	Maximum Cabled Attenuation (dB/km)
Core/Cladding Diameter (µm)	Minimum Laser EMB Bandwidth (MHz-km)
Numeric Aperture	Minimum OFL LED Bandwidth (MHz-km)
Proof Test Level (kpsi)	100

Installation and Operating Characteristics

Inner Cable		
	Installation	Operating
Max Tensile Load	1,400 N (310 lbs)	450 N (100 lbs)
Min Bend Radius	8.6 cm (3.4 in)	5.7 cm (2.2 in)
Outer Cable		
	Installation	Operating
Max Tensile Load	1,400 N (310 lbs)	450 N (100 lbs)
Min Bend Radius	17.1 cm (6.7 in)	11.4 cm (4.5 in)

Mechanical and Environmental

	Inner Cable	Entire Cable
Impact Resistance EIA/TIA-455-25A	1,500 Impacts	20 impacts (EIA-TIA-455-25A)
Crush Resistance TIA/EIA-455-41A	1,800 N/cm	440 N/cm (EIA-TIA-455-25A)
Flex Resistance	2,000 cycles	25 cycles
Operating Temperature	-40°C to +85°C	-40°C to +85°C
Storage Temperature	-55°C to +85°C	-55°C to +85°C
Installation Temperature (actual temp. of cable)	-10°C to +60°C	-10°C to +60°C
Flame Retardancy	UL Listed Type OFNR (UL 1666) and FT4 (CSA C22.2 No. 232)	

Cable Characteristics

Inner Cable	
Jacket Color	
Jacket Material	
Buffer Material	Hard Elastomeric
Cable Weight	31 kg/km (21 lbs/1000')
Cable Diameter	5.7 mm (0.22 in)
Outer Cable	
Jacket Color	
Jacket Material	
Cable Weight	118 kg/km (79 lbs/1000')
Cable Diameter	11.4 mm (0.45 in)

6 CHANNEL
D-Series Distribution Corrugated Steel Tape (CST) Armored
Cables

Part #: DX006



Standards

OCC CST armored tight-buffered fiber optic cables meet the functional requirements of the following standards:

- ICEA-S-104-696
- TIA-568
- TIA-598

Applications:

- Ideal for installation where direct-burial or rodent protection is required

Features:

- The steel armor is easily removed with an internal ripcord, leaving a fully functional intact riser-rated inner cable, with original cable markings for identification.
- Armored jacket is an add-on option which can be applied to most outdoor and indoor/outdoor riser-rated cables
- Inner tight-buffered cable is suitable for direct field termination with standard optical connectors