

## EASY INSTALLATION IN UNDER 2 MINUTES

### FEATURES

- Mechanical Splice (index matching gel)
- Highly Stable & Reliable
- Perfect Performance
- Compact Package
- RoHS Compliant
- Finished Connector meets UL94-V0 Flammability Rating
- TIA/EIA 568-C.3 Compliant

### XPRESS ULTRA™ FIBER SC CONNECTOR

SPECIFICATION	SINGLE-MODE	MULTIMODE
<b>For Xpress Ultra SC</b>	<b>TYPICAL</b>	
Insertion Loss	0.2dB (PC) and 0.3dB (APC)	0.1dB
Return Loss	55dB (PC), 60dB (APC)	35dB
Durability	<0.1dB change, 500 matings	
Operating Temperature	-40°C to +75°C	
Tensile	TIA/EIA 568-B.3	
Intermateability	IEC 61754-4	

*Note: Specifications shown above were obtained using OCC recommended products and procedures.*



DESCRIPTION	OCC PART #	HOUSING	BOOT COLOR
Fiber Conn, Pre-Polished, SC, 62.5, 250/900	<b>RFC-SC6</b>	Beige	White
Fiber Conn, Pre-Polished, SC, OM3/OM4, 250/900	<b>RFC-SC5G</b>	Aqua	White
Fiber Conn, Pre-Polished, SC, SM, 250/900	<b>RFC-SC8</b>	Blue	White
Fiber Conn, Pre-Polished, SC, APC, 250/900	<b>RFC-SCAPC</b>	Green	White
Fiber Conn, Pre-Polished, SC, 62.5, 2/3mm	<b>RFC-SC6-2/3MM</b>	Beige	White
Fiber Conn, Pre-Polished, SC, OM3/OM4, 2/3mm	<b>RFC-SC5G-2/3MM</b>	Aqua	White
Fiber Conn, Pre-Polished, SC, SM, 2/3mm	<b>RFC-SC8-2/3MM</b>	Blue	White
Fiber Conn, Pre-Polished, SC, APC, 2/3mm	<b>RFC-SCAPC-2/3MM</b>	Green	White



### FEATURES

- Mechanical Splice (index matching gel)
- Highly Stable & Reliable
- Perfect Performance
- Compact Package
- RoHS Compliant
- Finished Connector meets UL94-V0 Flammability Rating
- TIA/EIA 568-C.3 Compliant

### XPRESS ULTRA™ FIBER LC CONNECTOR

SPECIFICATION	SINGLE-MODE	MULTIMODE
<b>For Xpress Ultra LC</b>	<b>TYPICAL</b>	
Insertion Loss	0.2dB (PC) and 0.3dB (APC)	0.1dB
Return Loss	55dB (PC), 60dB (APC)	35dB
Durability	<0.1dB change, 500 matings	
Operating Temperature	-40°C to +75°C	
Tensile	TIA/EIA 568-B.3	
Intermateability	IEC 61754-4	

*Note: Specifications shown above were obtained using OCC recommended products and procedures.*

# XPRESS ULTRA FIBER CONNECTOR



**EASY INSTALLATION IN UNDER 2 MINUTES**

## XPRESS ULTRA™ FIBER LC CONNECTOR

DESCRIPTION	OCC PART #	HOUSING	BOOT COLOR
Fiber Conn, Pre-Polished, LC, 62.5, 250/900	<b>RFC-LC6</b>	Beige	White
Fiber Conn, Pre-Polished, LC, OM3/OM4, 250/900	<b>RFC-LC5G</b>	Aqua	White
Fiber Conn, Pre-Polished, LC, SM, 250/900	<b>RFC-LC8</b>	Blue	White
Fiber Conn, Pre-Polished, LC, APC, 250/900	<b>RFC-LCAPC</b>	Green	White
Fiber Conn, Pre-Polished, LC, 62.5, 2/3mm	<b>RFC-LC6-2/3MM</b>	Beige	White
Fiber Conn, Pre-Polished, LC, OM3/OM4, 2/3mm	<b>RFC-LC5G-2/3MM</b>	Aqua	White
Fiber Conn, Pre-Polished, LC, SM, 2/3mm	<b>RFC-LC8-2/3MM</b>	Blue	White
Fiber Conn, Pre-Polished, LC, APC, 2/3mm	<b>RFC-LCAPC-2/3MM</b>	Green	White



DESCRIPTION	OCC PART #
Xpress Ultra™ Field Installation Kit (Includes All Items)	<b>RFCTK</b>
250µm / 125µm Fiber Stripper	<b>RFCFS</b>
Thermal Buffer Removal Tool	<b>RFCTBRT</b>
Replacement Blade Set	<b>RFCTBRB</b>
Lint Free Dry Wipes (Box)	<b>RFCLFDW</b>
Fiber Optic Cleaning Pen	<b>RFCCP</b>
Kevlar Scissors	<b>RFCKS</b>
Fiber Disposal Unit	<b>RFCFD</b>
Fine Permanent Marker Pen	<b>RFCPMP</b>
Visible Fault Locator	<b>RFCSMS</b>
2.5mm to 1.25mm Adapter	<b>RFCSADAPT</b>
Launch Cable Test Kit	<b>RFCLCB</b>
OCC Soft Case & Termination Pad	<b>RFCCASE</b>
Precision Cleave Tool	<b>RFCCL</b>



### OCC ROANOKE, VA

**Corporate Headquarters and Fiber Optic Cable Manufacturing Facility**

5290 Concourse Drive  
Roanoke, VA 24019 USA

**540-265-0690 or 800-622-7711**

### OCC DALLAS, TX

**Harsh Environment and Specialty Connectivity Manufacturing Facility**

1700 Capital Avenue, Suite 150  
Plano, TX 75074 USA

**972-509-1500 or 877-509-1500**

### OCC ASHEVILLE, NC

**Enterprise Connectivity Manufacturing Facility**

33 Superior Way  
Swannanoa, NC 28778 USA

**828-298-2260 or 800-880-7674**