



kramer

TBUS-1AxI

Table Mount Modular Multi-Connection
Solution – Tilt-Up Lid



The TBUS-1AxI is the enclosure of a new modular system with a tilt-up lid. A complete TBUS system requires the enclosure, an inner frame, a power socket, inserts and a power cord.

NOTE: The TBUS enclosure, power socket, power cord & inserts are purchased separately

FEATURES

Cover - Manually opens & closes

Inner Frame - 6 different "TIAF" inner frame options are available that can accommodate a combination of up to 4 power sockets, 6 cable pass-through or connector inserts, 1 long insert and up to 3 Kramer TOOLS

Power Sockets - 8 different "TS" single and 8 dual power socket options are available to accommodate the power requirements worldwide

Power Cord - 8 different "C-AC" single power cords (and 3 "Y" power cords) for each power socket

Optional Accessories - TBUS Brackets, K-Able Box Cable Reels, Step-In Modules and Controllers are available

UL and CE Qualified

Connector Depth - Adjustable

Installation Requirement - Table cutout of 19.1cm x 15.2cm (7.51in x 5.98in)

Dimensions - 20.5cm x 17cm x 13.2cm (8.1" x 6.7" x 5.2") W, D, H

Weight - TBUS-1AxI: 1.5kg (3.3lbs) approx.; table clamps: 0.26kg (0.57lbs); metal template: 0.125kg (0.28lbs)



kramer

TECHNICAL SPECIFICATIONS

OPERATING TEMPERATURE RANGE:	+5° to +45°C
OPERATING HUMIDITY RANGE:	10 to 90% RHL, non-condensing
STORAGE TEMPERATURE RANGE:	-20° to +70°C
STORAGE HUMIDITY RANGE:	5 to 95% RHL, non-condensing
DIMENSIONS:	20.5cm x 17cm x 13.2cm (8.07" x 6.69" x 5.20") W, D, H
WEIGHT:	TBUS-1A: 1.5kg (3.3lbs) approx., table clamps: 0.26kg (0.57lbs), metal template: 0.125kg (0.28lbs)
INCLUDED ACCESSORIES:	Six self-locking ties
OPTIONS:	Inner frames, power sockets



kramer

CONFIGURATIONS

TBUS-1Axl(B)	Enclosure — Black Sand Blasted Anodized Aluminum Top
TBUS-1Axl(BC)	Enclosure — Silver Sand Blasted Anodized Aluminum Top
TBUS-1Axl(BA)	Enclosure — Silver Brushed Anodized Aluminum Top
